# Product datasheet

Specifications

Green Premium™

FRONT PLATE VIGI NSX630 VERTICAL FIXED TOGGLE W300 10M

03299

⚠ Discontinued on: 9 Aug 2023

⚠ **Discontinued**

EAN Code: 3303430032991

Main

Range	Prisma
Range Of Product	Prisma G Prisma P
Product Or Component Type	Front plate
Accessory / Separate Part Category	Installation accessory
Range Compatibility	Prisma Prisma G duct Prisma Prisma P cubicle
Type Of Front Plate	Cut-out
Installed Device	ComPact: fixed NSX400 with earth leakage protection - control: toggle - vertical installation ComPact: plug-in NSX400 with earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX630 with earth leakage protection - control: toggle - vertical installation ComPact: plug-in NSX630 with earth leakage protection - control: toggle - vertical installation
Poles Description	1 x 4P: mounting plate support: NSX400 vertical installation 1 x 3P: mounting plate support: NSX400 vertical installation 1 x 3P: mounting plate support: NSX630 vertical installation 1 x 4P: mounting plate support: NSX630 vertical installation
Operating Position	Vertical

Complementary

Enclosure/Cubicle Description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm Cubicle duct - width 400 mm depth 400 mm
Connection Position	Direct connection Front connection
Number Of Vertical Modules [50 Mm]	9
Standards	IEC 61439-1 IEC 61439-2
Product Certifications	ASEFA
Material	Steel
Surface Finish	Matt Smooth
Protective Treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9001)
Height	500 mm

Width	250 mm
Net Weight	1 kg
Quantity Per Set	Set of 1
Functional Unit	300 mm Prisma G floor-standing duct ComPact NSX400 with fixed toggle vertical 4P 1 direct
	300 mm Prisma G wall-mounted duct ComPact NSX400 with fixed toggle vertical 4P 1 direct
	400 mm 400 mm Prisma P cubicle ComPact NSX400 with fixed toggle vertical 3P 1 front connection 14
	400 mm 400 mm Prisma P cubicle ComPact NSX400 with fixed toggle vertical 4P 1 front connection 14
	400 mm 400 mm Prisma P cubicle ComPact NSX400 with plug-in toggle vertical 3P 1 front connection 14
	400 mm 400 mm Prisma P cubicle ComPact NSX400 with plug-in toggle vertical 4P 1 front connection 14
	400 mm 400 mm Prisma P cubicle ComPact NSX630 with fixed toggle vertical 3P 1 front connection 14
	400 mm 400 mm Prisma P cubicle ComPact NSX630 with fixed toggle vertical 4P 1 front connection 14
	400 mm 400 mm Prisma P cubicle ComPact NSX630 with plug-in toggle vertical 3P 1 front connection 14
	400 mm 400 mm Prisma P cubicle ComPact NSX630 with plug-in toggle vertical 4P 1 front connection 14
	300 mm Prisma G floor-standing duct ComPact NSX400 with fixed toggle vertical 3P 1 direct with long terminal shield 14
	300 mm Prisma G wall-mounted duct ComPact NSX400 with fixed toggle vertical 3P 1 direct with long terminal shield 14
	300 mm Prisma G floor-standing duct ComPact NSX400 with fixed toggle vertical 4P 1 direct with long terminal shield 14
	300 mm Prisma G wall-mounted duct ComPact NSX400 with fixed toggle vertical 4P 1 direct with long terminal shield 14
	300 mm Prisma G floor-standing duct ComPact NSX630 with fixed toggle vertical 3P 1 direct with long terminal shield 14
	300 mm Prisma G wall-mounted duct ComPact NSX630 with fixed toggle vertical 3P 1 direct with long terminal shield 14
	300 mm Prisma G floor-standing duct ComPact NSX630 with fixed toggle vertical 4P 1 direct with long terminal shield 14
	300 mm Prisma G wall-mounted duct ComPact NSX630 with fixed toggle vertical 4P 1 direct with long terminal shield 14

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.700 cm
Package 1 Width	26.000 cm
Package 1 Length	51.000 cm
Package 1 Weight	992.000 g
Unit Type Of Package 2	CAR
Number Of Units In Package 2	10
Package 2 Height	16.500 cm
Package 2 Width	27.900 cm
Package 2 Length	52.800 cm
Package 2 Weight	10.188 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	270
Package 3 Height	93.500 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm

Package 3 Weight	287.076 kg

Contractual warranty

Warranty	18 months

Sustainability ![Green Premium]

Green Premium^{TM} label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium ›

Guide to assess a product's sustainability ›

Transparency   RoHS/REACh

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information   Yes

✓ Halogen Free Plastic Parts Product

Certifications & Standards

Eu Rohs Directive   Pro-active compliance (Product out of EU RoHS legal scope)

EU RoHS Declaration

China Rohs Regulation   China RoHS declaration

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure   Product Environmental Profile