Product datasheet

Specification





PUSH BUTTON 600VAC 10A 30MM T-K

Local distributor code: 387206705

9001KR24BH13

EAN Code: 3389110913309

Main

Range Of Product	Harmony 9001K
Product Or Component Type	Push-button
Device Short Name	9001K
Type Of Operator	spring return
Operator Profile	Black mushroom Ø 35 mm. unmarked

Complementary

•					
Bezel Material	Metal				
Mounting Diameter	30 mm				
Cad Overall Width	46 mm				
Cad Overall Height	45 mm				
Cad Overall Depth	70 mm				
Terminals Description Iso N°1	(13-14-11-12)OF				
Net Weight	0.126 kg				
Operating Position	Any position				
Shape Of Signaling Unit Head	Round				
Head Material	Plastic				
Operator Additional Information	Screw-on plastic with set screw				
Contacts Type And Composition	1 C/O				
Positive Opening	Without				
Mechanical Durability	5000000 cycles				
Connections - Terminals	Screw clamp terminals, 1 x 0.222 x 1.5 mm² conforming to IEC 60947-1				
Tightening Torque	0.8 N.m conforming to IEC 60947-1				
Shape Of Screw Head	Cross slotted				
Contacts Material	Silver alloy contacts				
Short-Circuit Protection	10 A cartridge fuse conforming to IEC 60947-5-1				
[Ith] Conventional Free Air Thermal Current	10 A				
[Ui] Rated Insulation Voltage	250 V (pollution degree 3) conforming to IEC 60947-1				
[Uimp] Rated Impulse Withstand Voltage	2.5 kV conforming to IEC 60947-1				
[le] Rated Operational Current	3 A at 240 V, AC-15, A600-Q600 conforming to NEMA 0.55 A at 125 V, DC-13, A600-Q600 conforming to NEMA				

[Icm] Rated Short-Circuit Making	15 kA at 480 V AC-15, 7200 VA
Capacity	15 kA at 600 V AC-15, 7200 VA
	30 kA at 125 V DC-13, 7200 VA
	30 kA at 240 V AC-15, 7200 VA
	60 kA at 120 V AC-15, 7200 VA
	60 kA at 250 V DC-13, 7200 VA
	0.1 kA at 600 V DC-13
Rated Breaking Capacity	3 kA at 240 V AC-15, 720 VA
	6 kA at 120 V AC-15, 720 VA
	1.2 kA at 600 V AC-15, 720 VA
	1.5 kA at 480 V AC-15, 720 VA
	0.1 kA at 600 V DC-13
	0.27 kA at 250 V DC-13
	0.55 kA at 125 V DC-13
Device Presentation	Complete product
Cap/Operator Or Lens Colour	Black
Operator Profile	Mushroom Ø 35 mm
Type Of Operator	Spring return
Size	30 mm

Environment

Protective Treatment	TC				
Ambient Air Temperature For Storage	-4070 °C				
Ambient Air Temperature For Operation	-2570 °C				
Overvoltage Category	Class II conforming to IEC 61140				
Ip Degree Of Protection	IP66 conforming to IEC 60529				
Nema Degree Of Protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 4 NEMA 6				
	IEC 60947-5-1 IEC 60947-1 IEC 60947-5-4 JIS C 4520 JIS C 852 UL 508 CSA C22.2 No 14				
Product Certifications	NEMA UL 508				
Vibration Resistance	7 gn (f= 2500 Hz) conforming to IEC 60068-2-6				
Shock Resistance	50 gn conforming to IEC 60068-2-27				

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.7 cm
Package 1 Width	9.3 cm
Package 1 Length	5.6 cm
Package 1 Weight	146 g
Unit Type Of Package 2	S01

Number Of Units In Package 2	24
Package 2 Height	15 cm
Package 2 Width	15 cm
Package 2 Length	40 cm
Package 2 Weight	3.681 kg

Contractual warranty

Warranty 18 months

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes


Certifications & Standards


Reach Regulation	REACh Declaration		
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)		
China Rohs Regulation	China RoHS declaration		
Environmental Disclosure	Product Environmental Profile		
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins		
Circularity Profile	No need of specific recycling operations		

9001KR24BH13

Dimensions Drawings

Dimensions






 \boldsymbol{e} panel thickness: 1 to 6 mm / 0.04 to 0.24 in. \boldsymbol{a} 28 mm / 1.10 in.

9001KR24BH13

Mounting and Clearance

Contact Block Mounting Position


Top and Rear views



- (1) It is possible to mount up to 3 levels of contacts blocks (maximum of 6 contacts blocks)
- (2) Operator
- (3) Locating notch
- (4) Side 1
- (5) Side 2

Panel Cut-Out

Clearance



Legend plate	a min.		b min.	
	mm	in.	mm	in.
9001KN2••	57.2	2.25	44.5	1.75
9001KN3••	57.2	2.25	50.8	2.00

Individual Cut-outs Details

2 alternatives

