Product datasheet

Specifications





iQuick PRD8r modular surge arrester - 1 pole + N - 350V - with remote transfer

Local distributor code: 397135523

A9L16298

EAN Code: 3606480387104

Main

Range Of Product Acti9 Product Name Acti9 iQuick PRD Product Or Component Type Surge arrester with pluggable cartridge Device Short Name iQuick PRD8r Device Application Distribution Standards EN 61643-11:2012 IEC 61643-11:2011 Product Certifications CE Quality Labels NF KEMA-KEUR Poles Description 1P + N Remote Signalling With Signal Contacts Composition 1 SD (1 C/O) Surge Arrester Type Electrical distribution network Earthing System TN-S TT		
Product Or Component Type Surge arrester with pluggable cartridge Device Short Name iQuick PRD8r Device Application Distribution Standards EN 61643-11:2012 IEC 61643-11:2011 Product Certifications CE Quality Labels NF KEMA-KEUR Poles Description 1P + N Remote Signalling With Signal Contacts Composition 1 SD (1 C/O) Surge Arrester Type Electrical distribution network Earthing System TN-S	Range Of Product	Acti9
Device Short Name iQuick PRD8r Device Application Distribution Standards EN 61643-11:2012 IEC 61643-11:2011 Product Certifications CE Quality Labels NF KEMA-KEUR Poles Description 1P + N Remote Signalling With Signal Contacts Composition 1 SD (1 C/O) Surge Arrester Type Electrical distribution network Earthing System TN-S	Product Name	Acti9 iQuick PRD
Device Application Distribution Standards EN 61643-11:2012 IEC 61643-11:2011 Product Certifications CE Quality Labels NF KEMA-KEUR Poles Description 1P + N Remote Signalling With Signal Contacts Composition 1 SD (1 C/O) Surge Arrester Type Electrical distribution network Earthing System TN-S	Product Or Component Type	Surge arrester with pluggable cartridge
Standards EN 61643-11:2012 IEC 61643-11:2011 Product Certifications CE Quality Labels NF KEMA-KEUR Poles Description 1P + N Remote Signalling With Signal Contacts Composition 1 SD (1 C/O) Surge Arrester Type Electrical distribution network Earthing System TN-S	Device Short Name	iQuick PRD8r
IEC 61643-11:2011 Product Certifications CE Quality Labels NF KEMA-KEUR Poles Description 1P + N Remote Signalling With Signal Contacts Composition 1 SD (1 C/O) Surge Arrester Type Electrical distribution network Earthing System TN-S	Device Application	Distribution
Quality Labels NF KEMA-KEUR Poles Description 1P + N Remote Signalling With Signal Contacts Composition 1 SD (1 C/O) Surge Arrester Type Electrical distribution network Earthing System TN-S	Standards	
KEMA-KEUR Poles Description 1P + N Remote Signalling With Signal Contacts Composition 1 SD (1 C/O) Surge Arrester Type Electrical distribution network Earthing System TN-S	Product Certifications	CE
Remote Signalling With Signal Contacts Composition 1 SD (1 C/O) Surge Arrester Type Electrical distribution network Earthing System TN-S	Quality Labels	
Signal Contacts Composition 1 SD (1 C/O) Surge Arrester Type Electrical distribution network Earthing System TN-S	Poles Description	1P + N
Surge Arrester Type Electrical distribution network Earthing System TN-S	Remote Signalling	With
Earthing System TN-S	Signal Contacts Composition	1 SD (1 C/O)
	Surge Arrester Type	Electrical distribution network
	Earthing System	

Complementary

Surge Arrester Class Type	Type 2 + 3
Surge Arrester Technology	MOV + GDT
[Ue] Rated Operational Voltage	230 V AC (+/- 10 %) at 50/60 Hz
[In] Nominal Discharge Current	Common mode: 2 kA (L/PE) Common mode: 2 kA (N/PE) Differential mode: 2 kA (L/N)
[Imax] Maximum Discharge Current	Common mode: 8 kA L/PE Common mode: 8 kA N/PE Differential mode: 8 kA L/N
[Uoc] Open Circuit Voltage	10 kV type 3 common mode L/PE 10 kV type 3 common mode N/PE 10 kV type 3 differential mode L/N
[Uc] Maximum Continuous Operating Voltage	Common mode: 264 V N/PE Common mode: 350 V L/PE Differential mode: 350 V L/N
Maximum [Up] Voltage Protection Level	Common mode <1.5 kV type 2 L/PE Common mode <1.7 kV type 2 N/PE Differential mode <1.2 kV type 2 L/N Common mode <1.4 kV type 3 L/PE Differential mode <1.4 kV type 3 L/N Common mode <1.5 kV type 3 N/PE

Disconnector Device Type	Integrated circuit breaker - Icu 25 kA
Signalling Circuit Voltage	2 A/250 V AC 50/60 Hz
Mounting Mode	Clip-on (DIN rail)
9 Mm Pitches	8
Height	94 mm
Width	72 mm
Depth	75.9 mm
Net Weight	0.43 kg
Colour	White (RAL 9003)
Connections - Terminals	Tunnel type terminal (downside) 2.525 mm² Tunnel type terminal (upside) 2.525 mm²
Tightening Torque	2.5 N.m

Environment

Ik Degree Of Protection	IK05 conforming to IEC 62262
Relative Humidity	595 %
Operating Altitude	2000 m
Ambient Air Temperature For Operation	-2560 °C
Ambient Air Temperature For Storage	-4070 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.0 cm
Package 1 Width	9.0 cm
Package 1 Length	10.0 cm
Package 1 Weight	488.0 g
Unit Type Of Package 2	\$03
Number Of Units In Package 2	27
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	13.889 kg

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Halogen Free Plastic Parts & Cables Product

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations