Product datasheet

Specifications





energy sensor, PowerTag Monoconnect 63A 3P top and bottom position

Local distributor code: 404618991

A9MEM1540

EAN Code: 3606480909153

Main

| IVIAIII | |
|------------------------------|--|
| Range Of Product | PowerLogic |
| Product Name | PowerTag A9 M63 |
| Product Or Component Type | Energy sensor |
| Poles | 3P |
| Maximum Current [Imax] | 63 A |
| [lb] Basic Current | 10 A |
| Starting Current | 40 mA |
| Saturation Current | 130 A |
| Product Specific Application | Circuit monitoring Cost allocation Load monitoring Overload alarm Energy management |
| Concentrator Compatibility | Acti9 Smartlink SI B Acti9 Smartlink SI D Acti9 PowerTag Link C Acti9 PowerTag Link Acti9 PowerTag Link Wiser IP module EcoStruxure Panel Server Universal EcoStruxure Panel Server Advanced PrismaSet Active |
| Range Compatibility | Acti 9 Acti9 iKQE RCBO Multi9 Multi9 C60 Multi9 Multi9 ID Multi9 Multi9 C32N Multi9 Multi9 C65 Acti 9 Acti9 iID Acti 9 Acti9 iID K Acti 9 Acti9 iK60 Acti 9 Acti9 iKQ Acti 9 Acti9 iKQ Acti 9 Acti9 iC60 Acti 9 Acti9 iC65 Acti 9 Acti9 iC60 Acti 9 Acti9 iC65 Acti 9 Acti9 iC65 Acti 9 Acti9 iC65 Acti 9 Acti9 iC65 Acti 9 Acti9 iC60 single terminal |
| Type Of Measurement | Active power Current Voltage Power factor Active energy |
| Accuracy Class | Class 1 current conforming to IEC 61557-12 Class 0.5 voltage conforming to IEC 61557-12 Class 1 active power conforming to IEC 61557-12 Class 1 active energy conforming to IEC 61557-12 Class 1 power factor conforming to IEC 61557-12 |
| Mounting Location | Top or bottom |

| Mounting Support | On circuit breaker |
|-----------------------------|---|
| Product Destination | Switchboard |
| Event Management | Voltage loss with measured current at voltage loss |
| Transmission Support Medium | Radio frequency 2.42.4835 GHz conforming to IEEE 802.15.4 |
| Emission Power | 10 mW |

Complementary

| Mounting Mode | By screws (terminals) |
|---|---|
| Electrical Connection (Voltage Sensing & Power Supply) | Connector tooth |
| Cable Cross Section | 1 rigid cable 1.516 mm² 2 stranded cable 1.52.5 mm² 2 rigid cable 1.52.5 mm² 1 stranded cable 1.516 mm² |
| Supply Voltage | 380415 V AC, +/- 20 %, between phases |
| Network Frequency | 50 Hz 60 Hz |
| Maximum Power Consumption | 2 VA |
| Standards | IEC 61557-12 IEC 61010-1 IEC 61010-2-030 IEC 61326-1 ETSI EN 300 328 ETSI EN 301 487-1 |
| Height | 16.5 mm |
| Width | 54 mm |
| Depth | 43 mm |
| Net Weight | 28 g |
| Colour | White (RAL 9003) |

Environment

| Quality Labels | CE |
|---------------------------------------|---|
| Directives | 2014/53/EU - radio equipment directive |
| Operating Altitude | 02000 m |
| Ambient Air Temperature For Operation | -2560 °C |
| Ambient Air Temperature For Storage | -4085 °C |
| Overvoltage Category | III conforming to IEC 61010-1 |
| Measurement Category | Category III conforming to IEC 61010-2-030 |
| Ip Degree Of Protection | IP20 conforming to IEC 60529 |
| Ik Degree Of Protection | IK05 |
| Pollution Degree | 3 |
| Relative Humidity | 095 % at 45 °C conforming to IEC 60721-3-3 |
| Vibration Resistance | 3M4 conforming to IEC 60721-3-3 |
| Electromagnetic Compatibility | Industrial electromagnetic environment conforming to IEC 61326-1 Radiated EMC conforming to ETSI EN 301 489-17 Electromagnetic emission conforming to IEC 62311 |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 5.000 cm |
| Package 1 Width | 6.000 cm |
| Package 1 Length | 8.500 cm |
| Package 1 Weight | 57.000 g |
| Unit Type Of Package 2 | S02 |
| Number Of Units In Package 2 | 48 |
| Package 2 Height | 15.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 2.986 kg |

Contractual warranty

Warranty 18 months

Sustainability Green Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | End of Life Information |