Specifications



# Vigi C120 - earth leakage add-on block - 2P - 30 mA - class AC

Local distributor code: 397540118

A9N18563

EAN Code: 3606480376269

#### Main

Product Or Component Type	Add-on residual current devices
Device Short Name	Vigi C120
Poles Description	2P
[In] Rated Current	125 A
Network Type	AC
Earth-Leakage Sensitivity	30 mA
Earth-Leakage Protection Time Delay	Instantaneous
Earth-Leakage Protection Class	Туре АС

### Complementary

Complementary	
Device Location In System	Outgoer
Network Frequency	50/60 Hz
[Ue] Rated Operational Voltage	230240 V AC 50/60 Hz
Residual Current Tripping Technology	Voltage independent
[Ui] Rated Insulation Voltage	500 V AC 50/60 Hz conforming to IEC 60947-1
[Uimp] Rated Impulse Withstand Voltage	6 kV conforming to IEC 60947-2
Mounting Mode	Clip-on
Mounting Support	35 mm symmetrical DIN rail
Electrical Connection To Mcb	By screws
9 Mm Pitches	7
Height	95 mm
Width	117 mm
Depth	73 mm
Net Weight	0.325 kg
Colour	White
Mechanical Durability	20000 cycles
Connections - Terminals	Tunnel type terminals 135 mm² flexible Tunnel type terminals 150 mm² rigid
Wire Stripping Length	15 mm
Tightening Torque	3.5 N.m

### **Environment**

Standards	EN 61009 IEC/EN 61009-2-1
Ip Degree Of Protection	IP20
Pollution Degree	3 conforming to IEC 60947-2
Ambient Air Temperature For Operation	-560 °C
Ambient Air Temperature For Storage	-4060 °C

## **Packing Units**

Unit Type Of Package 1PCENumber Of Units In Package 11Package 1 Height9.3 cmPackage 1 Width13.5 cmPackage 1 Length13.5 cmPackage 1 Weight431.0 gUnit Type Of Package 2\$03	
Package 1 Height9.3 cmPackage 1 Width13.5 cmPackage 1 Length13.5 cmPackage 1 Weight431.0 g	
Package 1 Width 13.5 cm   Package 1 Length 13.5 cm   Package 1 Weight 431.0 g	
Package 1 Length 13.5 cm   Package 1 Weight 431.0 g	
Package 1 Weight 431.0 g	
Unit Type Of Package 2 S03	
Number Of Units In Package 2 8	
Package 2 Height 30.0 cm	
Package 2 Width 30.0 cm	
Package 2 Length40.0 cm	
Package 2 Weight 3.892 kg	

## **Contractual warranty**

Warranty

18 months

### **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

#### Well-being performance

Mercury Free	
Rohs Exemption Information	Yes
Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins