

Vigi C120 - earth leakage add-on block - 2P - 300 mA - class AC

A9N18564

EAN Code: 3606480376276

(!) Discontinued

Main

| Product Or Component Type | Add-on residual current devices |
|-------------------------------------|---------------------------------|
| Device Short Name | Vigi C120 |
| Poles Description | 2P |
| [In] Rated Current | 125 A |
| Network Type | AC |
| Earth-Leakage Sensitivity | 300 mA |
| Earth-Leakage Protection Time Delay | Instantaneous |
| Earth-Leakage Protection Class | Type AC |

Complementary

| o o mpromomear y | |
|---|--|
| Device Location In System | Outgoer |
| Network Frequency | 50/60 Hz |
| [Ue] Rated Operational Voltage | 230415 V AC 50/60 Hz |
| Residual Current Tripping Technology | Voltage independent |
| [Ui] Rated Insulation Voltage | 500 V AC 50/60 Hz conforming to IEC 60947-1 |
| [Uimp] Rated Impulse Withstand Voltage | 6 kV conforming to IEC 60947-2 |
| Mounting Mode | Clip-on |
| Mounting Support | 35 mm symmetrical DIN rail |
| Electrical Connection To Mcb | By screws |
| 9 Mm Pitches | 7 |
| Height | 95 mm |
| Width | 117 mm |
| Depth | 73 mm |
| Net Weight | 0.325 kg |
| Colour | White |
| Mechanical Durability | 20000 cycles |
| Connections - Terminals | Tunnel type terminals 135 mm² flexible Tunnel type terminals 150 mm² rigid |
| Wire Stripping Length | 15 mm |
| Tightening Torque | 3.5 N.m |

Environment

| Standards | EN 61009 IEC/EN 61009-2-1 |
|---------------------------------------|------------------------------|
| Ip Degree Of Protection | IP20 |
| Pollution Degree | 3 conforming to IEC 60947-2 |
| Ambient Air Temperature For Operation | -560 °C |
| Ambient Air Temperature For Storage | -4060 °C |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|---------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 9.3 cm |
| Package 1 Width | 13.5 cm |
| Package 1 Length | 13.5 cm |
| Package 1 Weight | 371 g |
| Unit Type Of Package 2 | S03 |
| Number Of Units In Package 2 | 8 |
| Package 2 Height | 30 cm |
| Package 2 Width | 30 cm |
| Package 2 Length | 40 cm |
| Package 2 Weight | 3.45 kg |

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

| Mercury Free | | |
|----------------------------|---|--|
| Rohs Exemption Information | Yes | |
| Reach Regulation | | |
| Neadif Negalation | REACh Declaration | |
| Eu Rohs Directive | Compliant with Exemptions | |
| China Rohs Regulation | China RoHS declaration | |
| | Product out of China RoHS scope. Substance declaration for your information | |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins | |