Product datasheet

Specifications

, Green Premium™



① To be discontinued

voltage transformer - 230..400 V -1 x 115 V - 1600 VA

Local distributor code: 389706410

ABL6TS160G

(!) To be discontinued on: 30 May 2024

(!) To be end-of-service on: 30 May 2025

EAN Code: 3389110598018

Main

Range Of Product	Madisan Transformer Onliniand
	Modicon Transformer Optimized
Product Or Component Type	Safety and isolation transformer
Rated Power In Va	1600 VA
Input Voltage	230 V AC single phase, terminal(s): N-L1 400 V AC phase to phase, terminal(s): L1-L2
Output Voltage	115 V AC
Secondary Winding	Single
Protective Cover	Without
Ambient Air Temperature For Operation	-2050 °C

Complementary

breakers in Selection of Protection Against overvoltage, protection technology: with additional protection fuses or breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection Connections - Terminals For input connection: screw type terminals, connection capacity: 5 x 4 mm² A' For input ground connection: screw type terminals, connection capacity: 1 x 4 AWG 11 For output connection: screw type terminals, connection capacity: 2 x 4 mm² A' For output connection: screw type terminals, connection capacity: 2 x 4 mm² A' B' By 4 screws diameter: 7 mm on vertical panel, operating position: horizontal By 4 screws diameter: 7 mm on horizontal panel with derating to 90 %	e emprennentar y				
Network Frequency Limits 4763 Hz Input Voltage Tolerance +/- 15 V Efficiency 96 % Power Dissipation In W 66.7 W Output Sustained Overvoltage 2 % (no load, hot state) Maximum Voltage Drop At Rated 0.1 % Load 0.1 % No Load Losses 23.7 W Short-Circuit Voltage 0,0245 Output Protection Type Against overload, protection technology: with additional protection fuses or breakers in Selection of Protection Against overvoltage, protection technology: with additional protection fuses or breakers in Selection of Protection Against overvoltage, protection technology: with additional protection fuses or breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or breakers in Selection of Protection Connections - Terminals For input connection: screw type terminals, connection capacity: 1 x 4 AWG 11 For output connection: screw type terminals, connection capacity: 2 x 4 mm² / AWG 11 For output connection: screw type terminals, connection capacity: 2 x 4 mm² / AWG 11 For output connection: scre	Input Voltage Limits				
Input Voltage Tolerance +/- 15 V Efficiency 96 % Power Dissipation In W 66.7 W Output Sustained Overvoltage 2 % (no load, hot state) Maximum Voltage Drop At Rated 0.1 % Load 0.1 % No Load Losses 23.7 W Short-Circuit Voltage 0,0245 Output Protection Type Against overload, protection technology: with additional protection fuses or breakers in Selection of Protection Against overload, protection technology: with additional protection fuses or breakers in Selection of Protection Against overload, protection technology: with additional protection fuses or breakers in Selection of Protection Against overload, protection technology: with additional protection fuses or breakers in Selection of Protection Against overload, protection technology: with additional protection fuses or breakers in Selection of Protection Against overload, protection technology: with additional protection fuses or breakers in Selection of Protection Against overload, protection technology: with additional protection fuses or breakers in Selection of Protection Connections - Terminals For input ground connection: screw type terminals, connection capacity: 1 x 4 AWG 11 For output connection: screw type terminals, connection capacity: 2 x 4 mm² / AWG 11 For output connection: screw type terminals, connection capacity: 2 x 4 mm² / AWG 11 For output connection: screw type terminals, connection capacity:		360440 V			
Efficiency 96 % Power Dissipation In W 66.7 W Output Sustained Overvoltage 2 % (no load, hot state) Maximum Voltage Drop At Rated 0.1 % Load 0.1 % No Load Losses 23.7 W Short-Circuit Voltage 0,0245 Output Protection Type Against overload, protection technology: with additional protection fuses or breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or breakers in Selection of Protection Connections - Terminals For input connection: screw type terminals, connection capacity: 5 x 4 mm² A For input ground connection: screw type terminals, connection capacity: 1 x 4 AWG 11 For output connection: screw type terminals, connection capacity: 2 x 4 mm² / Marking CE Fixing Mode By 4 screws diameter: 7 mm on vertical panel, operating position: horizontal By 4 screws diameter: 7 mm on horizontal panel with derating to 90 %	Network Frequency Limits	4763 Hz			
Power Dissipation In W 66.7 W Output Sustained Overvoltage 2 % (no load, hot state) Maximum Voltage Drop At Rated Load 0.1 % No Load Losses 23.7 W Short-Circuit Voltage 0,0245 Output Protection Type Against overload, protection technology: with additional protection fuses or cir breakers in Selection of Protection Against overvoltage, protection technology: with additional protection fuses or breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection Connections - Terminals For input connection: screw type terminals, connection capacity: 5 x 4 mm² A For input ground connection: screw type terminals, connection capacity: 1 x 4 AWG 11 For output connection: screw type terminals, connection capacity: 2 x 4 mm² / Marking CE Fixing Mode By 4 screws diameter: 7 mm on vertical panel, operating position: horizontal By 4 screws diameter: 7 mm on horizontal panel with derating to 90 %	Input Voltage Tolerance	+/- 15 V			
Output Sustained Overvoltage 2 % (no load, hot state) Maximum Voltage Drop At Rated 0.1 % Load 0.1 % No Load Losses 23.7 W Short-Circuit Voltage 0,0245 Output Protection Type Against overload, protection technology: with additional protection fuses or cirbreakers in Selection of Protection Against overvoltage, protection technology: with additional protection fuses or breakers in Selection of Protection Against overvoltage, protection technology: with additional protection fuses or breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or breakers in Selection of Protection Connections - Terminals For input connection: screw type terminals, connection capacity: 5 x 4 mm² A For output connection: screw type terminals, connection capacity: 1 x 4 AWG 11 For output connection: screw type terminals, connection capacity: 2 x 4 mm² / Marking CE Fixing Mode By 4 screws diameter: 7 mm on vertical panel, operating position: horizontal By 4 screws diameter: 7 mm on horizontal panel with derating to 90 %	Efficiency	96 %			
Maximum Voltage Drop At Rated Load 0.1 % No Load Losses 23.7 W Short-Circuit Voltage 0,0245 Output Protection Type Against overload, protection technology: with additional protection fuses or cir breakers in Selection of Protection Against overvoltage, protection technology: with additional protection fuses or breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection Connections - Terminals For input connection: screw type terminals, connection capacity: 5 x 4 mm² A For input ground connection: screw type terminals, connection capacity: 1 x 4 AWG 11 For output connection: screw type terminals, connection capacity: 2 x 4 mm² / Ge Marking CE Fixing Mode By 4 screws diameter: 7 mm on vertical panel, operating position: horizontal By 4 screws diameter: 7 mm on horizontal panel with derating to 90 %	Power Dissipation In W	66.7 W			
Load 23.7 W Short-Circuit Voltage 0,0245 Output Protection Type Against overload, protection technology: with additional protection fuses or cirbreakers in Selection of Protection Against overvoltage, protection technology: with additional protection fuses or breakers in Selection of Protection Against overvoltage, protection technology: with additional protection fuses or breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection Connections - Terminals For input connection: screw type terminals, connection capacity: 5 x 4 mm² A For input ground connection: screw type terminals, connection capacity: 1 x 4 AWG 11 For output connection: screw type terminals, connection capacity: 2 x 4 mm² A Marking CE Fixing Mode By 4 screws diameter: 7 mm on vertical panel, operating position: horizontal By 4 screws diameter: 7 mm on horizontal panel with derating to 90 %	Output Sustained Overvoltage	2 % (no load, hot state)			
Short-Circuit Voltage 0,0245 Output Protection Type Against overload, protection technology: with additional protection fuses or cirbreakers in Selection of Protection Against overvoltage, protection technology: with additional protection fuses or breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection Connections - Terminals For input connection: screw type terminals, connection capacity: 5 x 4 mm² A For input ground connection: screw type terminals, connection capacity: 1 x 4 AWG 11 For output connection: screw type terminals, connection capacity: 2 x 4 mm² A Marking CE Fixing Mode By 4 screws diameter: 7 mm on vertical panel, operating position: horizontal By 4 screws diameter: 7 mm on horizontal panel with derating to 90 %		0.1 %			
Output Protection Type Against overload, protection technology: with additional protection fuses or cirbreakers in Selection of Protection Against overvoltage, protection technology: with additional protection fuses or breakers in Selection of Protection Against overvoltage, protection technology: with additional protection fuses or breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection Connections - Terminals For input connection: screw type terminals, connection capacity: 5 x 4 mm² A For input ground connection: screw type terminals, connection capacity: 1 x 4 AWG 11 For output connection: screw type terminals, connection capacity: 2 x 4 mm² A Marking CE Fixing Mode By 4 screws diameter: 7 mm on vertical panel, operating position: horizontal By 4 screws diameter: 7 mm on horizontal panel with derating to 90 %	No Load Losses	23.7 W			
breakers in Selection of Protection Against overvoltage, protection technology: with additional protection fuses or breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection Connections - Terminals For input connection: screw type terminals, connection capacity: 5 x 4 mm² A' For input ground connection: screw type terminals, connection capacity: 1 x 4 AWG 11 For output connection: screw type terminals, connection capacity: 2 x 4 mm² A' For output connection: screw type terminals, connection capacity: 2 x 4 mm² A' By 4 screws diameter: 7 mm on vertical panel, operating position: horizontal By 4 screws diameter: 7 mm on horizontal panel with derating to 90 %	Short-Circuit Voltage	0,0245			
For input ground connection: screw type terminals, connection capacity: 1 x 4 AWG 11 For output connection: screw type terminals, connection capacity: 2 x 4 mm² / Marking CE Fixing Mode By 4 screws diameter: 7 mm on vertical panel, operating position: horizontal By 4 screws diameter: 7 mm on vertical panel, operating position: vertical By 4 screws diameter: 7 mm on horizontal panel with derating to 90 %	Output Protection Type	Against overvoltage, protection technology: with additional protection fuses or circ breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or			
Fixing Mode By 4 screws diameter: 7 mm on vertical panel, operating position: horizontal By 4 screws diameter: 7 mm on vertical panel, operating position: vertical By 4 screws diameter: 7 mm on horizontal panel with derating to 90 %	Connections - Terminals	For input connection: screw type terminals, connection capacity: 5 x 4 mm ² AWG 11 For input ground connection: screw type terminals, connection capacity: 1 x 4 mm ² AWG 11 For output connection: screw type terminals, connection capacity: 2 x 4 mm ² AWG 11			
By 4 screws diameter: 7 mm on vertical panel, operating position: vertical By 4 screws diameter: 7 mm on horizontal panel with derating to 90 %	Marking	CE			
	Fixing Mode	By 4 screws diameter: 7 mm on vertical panel, operating position: vertical			
Operating Altitude 3000 m	Operating Altitude	3000 m			

Electrical Insulation Class	Class B
Width	174.0 mm
Height	169.0 mm
Depth	163.0 mm
Net Weight	20.07 kg

Environment

Product Certifications	UR EAC DNV-GL			
Standards	UL 506			
Ip Degree Of Protection	IP20			
Environmental Characteristic	EMC conforming to EN 62041 Safety conforming to EN 61558-1 Safety conforming to EN 61558-2-4			
Protective Treatment	TC			
Ambient Air Temperature For Storage	-4080 °C			
Overvoltage Category	Class I conforming to VDE 0106-1			
Dielectric Strength	2000 V between winding and ground 4000 V between primary and secondary			

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	30.400 cm
Package 1 Width	40.200 cm
Package 1 Length	40.200 cm
Package 1 Weight	21.566 kg
Unit Type Of Package 2	P06
Number Of Units In Package 2	4
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	92.876 kg

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free


Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations Circularity Profile

Product datasheet

Dimensions Drawings

Dimensions



Dimensions in mm

а	b	с	G	J	Ø
174	163	169	135	141	7


Dimensions in in.

а	b	с	G	J	Ø
6.85	6.42	6.65	5.31	5.55	0.27


Product datasheet

Connections and Schema

Internal Scheme



Primary Voltage Wiring



17 May 2024

Secondary Voltage Wiring

