Product datasheet





TeSys K control relay - 2 NO + 2 NC - <= 690 V - 24 V AC coil

Local distributor code:

21169807 CA2KN22B7

EAN Code: 3389110500271

Main

| Range | TeSys | |
|--------------------------------|--------------------|--|
| Product Name | TeSys CAK | |
| Product Or Component Type | Control relay | |
| Device Short Name | CA2K | |
| Contactor Application | Control circuit | |
| Utilisation Category | DC-13 AC-15 | |
| Pole Contact Composition | 2 NO + 2 NC | |
| [Ue] Rated Operational Voltage | <= 690 V <= 400 Hz | |
| Control Circuit Type | AC at 50/60 Hz | |
| [Uc] Control Circuit Voltage | 24 V AC 50/60 Hz | |

Complementary

| oompicinental y | | |
|--|--|--|
| [Ith] Conventional Free Air Thermal Current | 10 A (at 50 °C) | |
| Irms Rated Making Capacity | 110 A conforming to IEC 60947 | |
| Associated Fuse Rating | 10 A gG conforming to IEC 60947 10 A gG conforming to VDE 0660 | |
| [Ui] Rated Insulation Voltage | 690 V conforming to IEC 60947 750 V conforming to VDE 0110 group C 690 V conforming to BS 5424 600 V conforming to CSA C22.2 No 14 | |
| Mounting Support | Plate Rail | |
| Connections - Terminals | Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 2 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.341.5 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible without cable end | |
| Tightening Torque | 1.3 N.m - on screw clamp terminals - with screwdriver Philips No 2 1.3 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm 1.3 N.m - on screw clamp terminals - with screwdriver pozidriv No 2 | |
| Control Circuit Voltage Limits | Drop-out: 0.20.75 Uc (at <50 °C) Operational: 0.81.15 Uc (at <50 °C) | |
| Operating Time | 1020 ms coil de-energisation and NO opening 1020 ms coil energisation and NO closing 1525 ms coil de-energisation and NC closing 515 ms coil energisation and NC opening | |
| Mechanical Durability | 10 Mcycles | |

Life Is On Schneider 19 Apr 2024

| Maximum Operating Rate | 10000 cyc/h | |
|---------------------------------|-------------------|--|
| Immunity To Microbreaks | 2 ms | |
| Inrush Power In Va | 30 VA (at 20 °C) | |
| Hold-In Power Consumption In Va | 4.5 VA (at 20 °C) | |
| Heat Dissipation | 1.3 W | |
| Minimum Switching Voltage | 17 V | |
| Minimum Switching Current | 5 mA | |
| Non Overlap Distance | 0.5 mm | |
| Insulation Resistance | > 10 MOhm | |
| Height | 58 mm | |
| Width | 45 mm | |
| Depth | 57 mm | |
| Net Weight | 0.18 kg | |

Environment

| Standards | EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 | |
|---------------------------------------|---|--|
| Product Certifications | CB Scheme CCC UL CSA EAC CE | |
| Ip Degree Of Protection | IP2X | |
| Protective Treatment | TC conforming to IEC 60068 | |
| Ambient Air Temperature For Operation | -2550 °C | |
| Ambient Air Temperature For Storage | -5080 °C | |
| Operating Altitude | 2000 m without derating | |
| Flame Retardance | V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102 | |
| Mechanical Robustness | Vibrations contactor open: 2 Gn, 5300 Hz conforming to IEC 60068-2-6 Vibrations contactor closed: 4 Gn, 5300 Hz conforming to IEC 60068-2-6 Shocks contactor open: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor closed: 15 Gn for 11 ms conforming to IEC 60068-2-27 | |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|---------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 7.0 cm |
| Package 1 Width | 6.2 cm |
| Package 1 Length | 4.9 cm |
| Package 1 Weight | 180.0 g |
| Unit Type Of Package 2 | S02 |

| Number Of Units In Package 2 | 50 |
|------------------------------|----------|
| Package 2 Height | 15.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 9.316 kg |
| Unit Type Of Package 3 | P06 |
| Number Of Units In Package 3 | 800 |
| Package 3 Height | 77.0 cm |
| Package 3 Width | 80.0 cm |
| Package 3 Length | 60.0 cm |
| Package 3 Weight | 152.0 kg |

Contractual warranty

Warranty 18 months

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| ⊘ | Reach Free Of Svhc | |
|----------|----------------------------|-----|
| ⊘ | Toxic Heavy Metal Free | |
| ⊘ | Mercury Free | |
| ⊘ | Rohs Exemption Information | Yes |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | End of Life Information |