Product datasheet

Specifications





TeSys K control relay - 4 NO - <= 690 V - 220 V DC standard coil

CA3KN40MD

EAN Code: 3389110484748

Main

Range	TeSys
Product Name	TeSys CAK
Product Or Component Type	Control relay
Device Short Name	САЗК
Contactor Application	Control circuit
Utilisation Category	AC-15 DC-13
Pole Contact Composition	4 NO
[Ue] Rated Operational Voltage	<= 690 V <= 400 Hz
Control Circuit Type	DC standard
[Uc] Control Circuit Voltage	220 V DC

Complementary

[Ith] Conventional Free Air Thermal Current	10 A (at 50 °C)
Irms Rated Making Capacity	110 A conforming to IEC 60947
Associated Fuse Rating	10 A gG conforming to IEC 60947 10 A gG conforming to VDE 0660
[Ui] Rated Insulation Voltage	690 V conforming to IEC 60947 750 V conforming to VDE 0110 group C 690 V conforming to BS 5424 600 V conforming to CSA C22.2 No 14
Mounting Support	Rail Plate
Connections - Terminals	Screw clamp terminals 1 cable(s) 1.54 mm ² solid Screw clamp terminals 2 cable(s) 1.54 mm ² solid Screw clamp terminals 1 cable(s) 0.754 mm ² flexible with cable end Screw clamp terminals 2 cable(s) 0.754 mm ² flexible without cable end Screw clamp terminals 1 cable(s) 0.341.5 mm ² flexible with cable end Screw clamp terminals 2 cable(s) 0.341.5 mm ² flexible without cable end
Tightening Torque	1.3 N.m - on screw clamp terminals - with screwdriver flat \emptyset 6 mm 1.3 N.m - on screw clamp terminals - with screwdriver Philips No 26 mm 1.3 N.m - on screw clamp terminals - with screwdriver pozidriv No 2
Control Circuit Voltage Limits	Operational: 0.81.15 Uc (at <50 °C) Drop-out: 0.10.75 Uc (at <50 °C)
Operating Time	10 ms coil de-energisation and NO opening 3040 ms coil energisation and NO closing
Mechanical Durability	20 Mcycles
Maximum Operating Rate	10000 cyc/h

Life Is On Schneider

Immunity To Microbreaks	2 ms
Inrush Power In W	3 W (at 20 °C)
Hold-In Power Consumption In W	3 W at 20 °C
Heat Dissipation	3 W
Minimum Switching Voltage	17 V
Minimum Switching Current	5 mA
Non Overlap Distance	0.5 mm
Insulation Resistance	> 10 MOhm
Height	58 mm
Width	45 mm
Depth	57 mm
Net Weight	0.225 kg

Environment

<u> </u>	
Standards	EN/IEC 60947-4-1
	GB/T 14048.4
	UL 60947-4-1
	CSA C22.2 No 60947-4-1
	JIS C8201-4-1
Product Certifications	CB Scheme
	CCC
	UL
	CSA
	EAC
	CE
	UKCA
Ip Degree Of Protection	IP2X
Protective Treatment	TC conforming to IEC 60068
Ambient Air Temperature For Operation	-2550 °C
Ambient Air Temperature For Storage	-5080 °C
Operating Altitude	2000 m without derating
Flame Retardance	V1 conforming to UL 94
	Requirement 2 conforming to NF F 16-101
	Requirement 2 conforming to NF F 16-102
	Requirement 2 comonning to NFF 10-102
Mechanical Robustness	Vibrations contactor open: 2 Gn, 5300 Hz conforming to IEC 60068-2-6
	Vibrations contactor closed: 4 Gn, 5300 Hz conforming to IEC 60068-2-6
	Shocks contactor open: 10 Gn for 11 ms conforming to IEC 60068-2-27
	Shocks contactor closed: 15 Gn for 11 ms conforming to IEC 60068-2-27
	Shorks contactor closed. 15 On 101 11 his contonning to 120 00000-2-21

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.500 cm
Package 1 Width	6.000 cm
Package 1 Length	6.500 cm
Package 1 Weight	211.000 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	40

Package 2 Height15.000 cmPackage 2 Width30.000 cmPackage 2 Length40.000 cmPackage 2 Weight8.674 kgUnit Type Of Package 3P06Number Of Units In Package 3640Package 3 Height75.000 cmPackage 3 Width80.000 cmPackage 3 Length60.000 cmPackage 3 Weight146.784 kg		
Package 2 Length40.000 cmPackage 2 Weight8.674 kgUnit Type Of Package 3P06Number Of Units In Package 3640Package 3 Height75.000 cmPackage 3 Width80.000 cmPackage 3 Length60.000 cm	Package 2 Height	15.000 cm
Package 2 Weight8.674 kgUnit Type Of Package 3P06Number Of Units In Package 3640Package 3 Height75.000 cmPackage 3 Width80.000 cmPackage 3 Length60.000 cm	Package 2 Width	30.000 cm
Unit Type Of Package 3 P06 Number Of Units In Package 3 640 Package 3 Height 75.000 cm Package 3 Width 80.000 cm Package 3 Length 60.000 cm	Package 2 Length	40.000 cm
Number Of Units In Package 3 640 Package 3 Height 75.000 cm Package 3 Width 80.000 cm Package 3 Length 60.000 cm	Package 2 Weight	8.674 kg
Package 3 Height 75.000 cm Package 3 Width 80.000 cm Package 3 Length 60.000 cm	Unit Type Of Package 3	P06
Package 3 Width 80.000 cm Package 3 Length 60.000 cm	Number Of Units In Package 3	640
Package 3 Length 60.000 cm	Package 3 Height	75.000 cm
	Package 3 Width	80.000 cm
Package 3 Weight 146.784 kg	Package 3 Length	60.000 cm
	Package 3 Weight	146.784 kg

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information