Product datasheet

Specifications





(!) Discontinued

TeSys GS - switch-disconnector fuse - 4 P - 160 A - DIN 00

GS1LLD4

() Discontinued on: 14 Dec 2020

EAN Code: 3389110253993

Main

TeSys	
TeSys GS	
GS1 L	
Switch-disconnector-fuse	
Protection	
4P	
4t	
4 NO	
160 A (at 40 °C)	
125 A at 440 V 2 poles in series per phase DC-23A 125 A at 440 V 2 poles in series per phase DC-23B 125 A at 690 V with terminal cover AC-23A 125 A at 690 V with terminal cover AC-23B 160 A at 400 V AC-23A 160 A at 400 V AC-23B 160 A at 500 V AC-23A 160 A at 500 V AC-23B	
DIN	
00	
DC AC	
50/60 Hz	

Complementary

Type Of Operating Handle	Direct right side
Mounting Support	Plate
[Ui] Rated Insulation Voltage	750 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage	8 kV
Rated Operational Power In W	90 kW at 400 V 110 kW at 500 V 110 kW at 690 V
Breaking Capacity	12 W
Making Capacity	1600 A at 400 V AC-23B
Breaking Capacity	1280 A at 400 V (AC-23B)
Short-Circuit Withstand	22.7 kA

Mechanical Durability	10000 cycles	
Electrical Durability	1000 cycles AC-23A 1000 cycles AC-23B 200 cycles DC-23A 200 cycles DC-23B	
Connections - Terminals	Power circuit: bars Power circuit: lugs-ring terminals5095 mm² flexible	
[Icm] Rated Short-Circuit Making Capacity	100 kA at 400 V with protection by gG fuses	
Tightening Torque	Power circuit: 12 N.m - on bars Power circuit: 12 N.m - on lugs-ring terminals	

Environment

Standards	
	IEC 60947-3
Product Certifications	CE
Protective Treatment	тн
Ip Degree Of Protection	IP20 conforming to IEC 60529 (with terminal cover)
Ambient Air Temperature For Operation	-2070 °C
Ambient Air Temperature For Storage	-4080 °C
Fire Resistance	850 °C fuse cover conforming to IEC 60695-2-1 960 °C body conforming to IEC 60695-2-1
Height	162 mm
Width	186 mm
Depth	126.5 mm
Net Weight	2.3 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	15.4 cm
Package 1 Width	17.4 cm
Package 1 Length	21.1 cm
Package 1 Weight	2.143 kg

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information