Product datasheet

Specifications





Straight length, Canalis KBA, 25 A, 1 circuit L+N+PE, remote control circuit, 3 tap-off units, 3 m, white

Local distributor code: 385363970

KBA25ED2303TW

EAN Code: 3606480000065

Main

Range Of Product	Canalis
Device Short Name	КВА
Offer Type	Control system
Product Or Component Type	Straight length
Busbar Description	Distribution length
Device Application	Lighting Power socket distribution
[le] Rated Operational Current	25 A at 35 °C
[Ue] Rated Operational Voltage	230400 V
Network Frequency	50/60 Hz
Busbar Trunking Polarity	L + N + PE
Number Of Circuits	1
Number Of Tap-Off Outlets	3
Control Type	Communicating
Communication Port Protocol	KNX
Mounting Mode	By clips

Complementary

[Uimp] Rated Impulse Withstand Voltage	4 kV
[Ui] Rated Insulation Voltage	690 V
[Icw] Rated Short-Time Withstand Current	0.44 kA
[lpk] Rated Peak Withstand Current	4.4 kA
Thermal Stress Limit	195 kA ² .s
Maximum Radiated Magnetic Field	2 pT
Thdi	015 % 25 A 1533 % 20 A 33100 % 16 A
Maximum Voltage Drop	<0.72 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.67 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.61 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.54 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
Standards	EN/IEC 61439-6 EN/IEC 61439-1
Width	30 mm

Height	46 mm
Length	3 m
Colour	White (RAL 9003)
Net Weight	2.4 ka

Environment

Ip Degree Of Protection	IP55 conforming to EN/IEC 60529
Ik Degree Of Protection	IK06 conforming to EN/IEC 62262
Ambient Air Temperature For Operation	035 °C (100 % of In) 3540 °C (96 % of In) 4045 °C (93 % of In) 4550 °C (89 % of In) 5055 °C (85 % of In)

Packing Units

Unit Type Of Package 1 Package 1 Height Package 1 Height Package 1 Width 3 cm Package 1 Length 300 cm Package 1 Weight 2.5 kg Unit Type Of Package 2 BB1 Number Of Units In Package 2 Fackage 2 Height 10.5 cm Package 2 Weight 10.5 cm Package 2 Unit Type Of Package 3 Package 2 Height 10.5 cm Package 2 Weight 15 kg Unit Type Of Package 3 Package 3 Height 55 cm Package 3 Height 55 cm Package 3 Weight 15 kg Package 3 Height 55 cm Package 3 Weight 15 kg		
Package 1 Height 4.6 cm Package 1 Width 3 cm Package 1 Length 300 cm Package 1 Weight 2.5 kg Unit Type Of Package 2 BB1 Number Of Units In Package 2 6 Package 2 Height 10.5 cm Package 2 Width 10.5 cm Package 2 Length 318 cm Package 2 Weight 15 kg Unit Type Of Package 3 PAL Number Of Units In Package 3 144 Package 3 Height 55 cm Package 3 Width 63 cm Package 3 Length 318 cm	Unit Type Of Package 1	PCE
Package 1 Width 3 cm Package 1 Length 300 cm Package 1 Weight 2.5 kg Unit Type Of Package 2 BB1 Number Of Units In Package 2 6 Package 2 Height 10.5 cm Package 2 Width 10.5 cm Package 2 Length 318 cm Package 2 Weight 15 kg Unit Type Of Package 3 PAL Number Of Units In Package 3 144 Package 3 Height 55 cm Package 3 Width 63 cm Package 3 Width 63 cm	Number Of Units In Package 1	1
Package 1 Length 300 cm Package 1 Weight 2.5 kg Unit Type Of Package 2 BB1 Number Of Units In Package 2 6 Package 2 Height 10.5 cm Package 2 Width 10.5 cm Package 2 Length 318 cm Package 2 Weight 15 kg Unit Type Of Package 3 PAL Number Of Units In Package 3 144 Package 3 Height 55 cm Package 3 Width 63 cm Package 3 Length 318 cm	Package 1 Height	4.6 cm
Package 1 Weight 2.5 kg Unit Type Of Package 2 BB1 Number Of Units In Package 2 6 Package 2 Height 10.5 cm Package 2 Width 10.5 cm Package 2 Length 318 cm Package 2 Weight 15 kg Unit Type Of Package 3 PAL Number Of Units In Package 3 144 Package 3 Height 55 cm Package 3 Width 63 cm Package 3 Length 318 cm	Package 1 Width	3 cm
Unit Type Of Package 2 BB1 Number Of Units In Package 2 Package 2 Height 10.5 cm Package 2 Width 10.5 cm Package 2 Length 318 cm Package 2 Weight 15 kg Unit Type Of Package 3 PAL Number Of Units In Package 3 144 Package 3 Height 55 cm Package 3 Width 63 cm Package 3 Length 318 cm	Package 1 Length	300 cm
Number Of Units In Package 2 6 Package 2 Height 10.5 cm Package 2 Width 10.5 cm Package 2 Length 318 cm Package 2 Weight 15 kg Unit Type Of Package 3 PAL Number Of Units In Package 3 144 Package 3 Height 55 cm Package 3 Width 63 cm Package 3 Length 318 cm	Package 1 Weight	2.5 kg
Package 2 Height 10.5 cm Package 2 Width 10.5 cm Package 2 Length 318 cm Package 2 Weight 15 kg Unit Type Of Package 3 PAL Number Of Units In Package 3 144 Package 3 Height 55 cm Package 3 Width 63 cm Package 3 Length 318 cm	Unit Type Of Package 2	BB1
Package 2 Width 10.5 cm Package 2 Length 318 cm Package 2 Weight 15 kg Unit Type Of Package 3 PAL Number Of Units In Package 3 144 Package 3 Height 55 cm Package 3 Width 63 cm Package 3 Length 318 cm	Number Of Units In Package 2	6
Package 2 Length 318 cm Package 2 Weight 15 kg Unit Type Of Package 3 PAL Number Of Units In Package 3 144 Package 3 Height 55 cm Package 3 Width 63 cm Package 3 Length 318 cm	Package 2 Height	10.5 cm
Package 2 Weight 15 kg Unit Type Of Package 3 PAL Number Of Units In Package 3 144 Package 3 Height 55 cm Package 3 Width 63 cm Package 3 Length 318 cm	Package 2 Width	10.5 cm
Unit Type Of Package 3 PAL Number Of Units In Package 3 144 Package 3 Height 55 cm Package 3 Width 63 cm Package 3 Length 318 cm	Package 2 Length	318 cm
Number Of Units In Package 3 144 Package 3 Height 55 cm Package 3 Width 63 cm Package 3 Length 318 cm	Package 2 Weight	15 kg
Package 3 Height 55 cm Package 3 Width 63 cm Package 3 Length 318 cm	Unit Type Of Package 3	PAL
Package 3 Width 63 cm Package 3 Length 318 cm	Number Of Units In Package 3	144
Package 3 Length 318 cm	Package 3 Height	55 cm
	Package 3 Width	63 cm
Package 3 Weight 444 kg	Package 3 Length	318 cm
- doings o troight 444 kg	Package 3 Weight	444 kg

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc
9	Toxic Heavy Metal Free
②	Mercury Free
Ø	Rohs Exemption Information Yes
⊘	Pvc Free
9	Halogen Free Product

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations