Product datasheet

Specifications



FLEXIBLE LENGTH 40A 2M

Local distributor code:

385364144 KBA40DF420TW



EAN Code: 3606480000362

Main

| Range Of Product | Canalis | |
|--------------------------------|---------------------------------------|--|
| Product Name | КВА | |
| Offer Type | Control system | |
| Product Or Component Type | Flexible element | |
| Busbar Description | Flexible length | |
| Device Application | Power socket distribution Lighting | |
| Direction Change Type | 3 dimensions | |
| [le] Rated Operational Current | 40 A at 35 °C 25 A | |
| [Ue] Rated Operational Voltage | 230400 V | |
| Network Frequency | 50/60 Hz | |
| Number Of Circuits | 1 | |
| Busbar Trunking Polarity | 3L + N + PE | |
| Control Type | Communicating | |
| Communication Port Protocol | DALI KNX | |
| Colour | White (RAL 9003) | |

Complementary

| Mounting Mode | By clips |
|--|---|
| Thermal Stress Limit | 900 kA².s |
| Maximum Radiated Magnetic Field | 2 pT |
| [Uimp] Rated Impulse Withstand Voltage | 4 kV |
| [Ui] Rated Insulation Voltage | 690 V |
| [Icw] Rated Short-Time Withstand Current | 0.94 kA |
| [lpk] Rated Peak Withstand Current | 9.6 kA |
| Thdi | 015 % 40 A 1533 % 32 A 33100 % 28 A |
| Length | 2 m |
| Depth | 30 mm |
| Height | 46 mm |

| Net Weight | 105 g |
|------------|----------------------------|
| Standards | IEC 61439-1 IEC 61439-6 |

Environment

| Ip Degree Of Protection | IP55 conforming to IEC 60529 |
|--|------------------------------|
| Ik Degree Of Protection | IK06 conforming to IEC 62262 |
| Ambient Air Temperature For Operation | 035 °C without derating |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|---------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 6.0 cm |
| Package 1 Width | 44.0 cm |
| Package 1 Length | 61.0 cm |
| Package 1 Weight | 1.72 kg |

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| ② | Reach Free Of Svhc |
|----------|--------------------------------|
| ⊘ | Toxic Heavy Metal Free |
| Ø | Mercury Free |
| 9 | Rohs Exemption Information Yes |
| ⊘ | Pvc Free |
| 9 | Halogen Free Product |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | No need of specific recycling operations |