Product datasheet

Specification





Straight length, Canalis KBA, 40 A, 1 circuit 3L+N+PE, 3 tap-off units, 3 m, white

Local distributor code: 21468825

KBA40ED4303W

EAN Code: 3606480000553

Main

| Range Of Product | Canalis | |
|--------------------------------|------------------------------------|--|
| Device Short Name | KBA | |
| Offer Type | Classic Control system | |
| Product Or Component Type | nponent Type Straight length | |
| Busbar Description | Distribution length | |
| Device Application | Lighting Power socket distribution | |
| [le] Rated Operational Current | 40 A at 35 °C | |
| [Ue] Rated Operational Voltage | 230400 V | |
| Network Frequency | k Frequency 50/60 Hz | |
| Busbar Trunking Polarity | par Trunking Polarity 3L + N + PE | |
| Number Of Circuits | ber Of Circuits 1 | |
| Number Of Tap-Off Outlets | Of Tap-Off Outlets 3 | |
| Control Type | Communicating | |
| Communication Port Protocol | on Port Protocol DALI | |
| Mounting Mode | By clips | |

Complementary

| • | | |
|--|--|--|
| [Uimp] Rated Impulse Withstand Voltage | 4 kV | |
| [Ui] Rated Insulation Voltage | 690 V | |
| [Icw] Rated Short-Time Withstand Current | 0.94 kA | |
| [lpk] Rated Peak Withstand Current | | |
| Thermal Stress Limit | 900 kA ² .s | |
| Maximum Radiated Magnetic Field | 2 pT | |
| Thdi | 015 % 40 A 1533 % 32 A 33100 % 28 A | |
| Maximum Voltage Drop | <0.3 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.28 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.25 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.22 V with power factor = 0.7 at 50 Hz with 1A for 100 m long | |
| Standards | EN/IEC 61439-6 EN/IEC 61439-1 | |
| Width | 30 mm | |

| Height | 46 mm | |
|------------|------------------|--|
| Length | 3 m | |
| Colour | White (RAL 9003) | |
| Net Weight | 3.1 kg | |

Environment

| Ip Degree Of Protection | IP55 conforming to EN/IEC 60529 | |
|---------------------------------------|--|--|
| Ik Degree Of Protection | IK06 conforming to EN/IEC 62262 | |
| Ambient Air Temperature For Operation | 035 °C (100 % of In) 3540 °C (96 % of In) 4045 °C (93 % of In) 4550 °C (89 % of In) 5055 °C (85 % of In) | |

Packing Units

| PCE 1 |
|------------|
| 1 |
| |
| 3.400 cm |
| 4.700 cm |
| 314.000 cm |
| 3.000 kg |
| BB1 |
| 6 |
| 10.700 cm |
| 10.600 cm |
| 319.000 cm |
| 19.000 kg |
| PAL |
| 144 |
| 53.000 cm |
| 64.000 cm |
| 320.000 cm |
| 476.000 kg |
| |

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| ⊘ | Reach Free Of Svhc |
|----------|--------------------------------|
| ⊘ | Toxic Heavy Metal Free |
| ⊘ | Mercury Free |
| ⊘ | Rohs Exemption Information Yes |
| ⊘ | Halogen Free Product |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | No need of specific recycling operations |

Product datasheet

KBA40ED4303W

Dimension Drawings

