Product datasheet

Specifications



TAPOFF UNIT 32A FOR MODULAR EQUIPMENT

Local distributor code: 2224538

KNB32CM55

IN DOZOMO

EAN Code: 3606480006197

Main

Range Of Product	Canalis
Range Compatibility	Canalis KN busbar trunking
Product Or Component Type	Tap-off unit
Busbar Trunking Compatibility	Canalis KN busbar trunkingplug-in
[le] Rated Operational Current	32 A
Protection Type	Circuit breaker: miniature circuit breaker (MCB)
Mounting Mode	Plug-in with fixed polarity
Tap-Off Unit Polarity	3L+N+PE
Colour	White (RAL 9001)

Complementary

Complementary	
Device Application	Low power distribution
Provided Equipment	5 circuit-breaker to be ordered separately blanking plate
[Ue] Rated Operational Voltage	230500 V depending on protective device
[Uimp] Rated Impulse Withstand Voltage	4.6 kV
[Ui] Rated Insulation Voltage	400 V depending on protective device 500 V depending on protective device
Network Frequency	50/60 Hz
Electrical Connection	Pre-wired terminal block - ISO32 6 mm² flexible Pre-wired terminal block - ISO32 10 mm² rigid
Door/Cover Opening Side	Front
Tap-Off Unit Disconnection Mode	By drawing out
Standards	IEC 61439-6 IEC 61439-1
18 Mm Pitches	5
Width	135 mm
Depth	95 mm
Height	165 mm
Net Weight	0.6 kg

Environment

Earthing System	TT TN-S IT
Ip Degree Of Protection	IP55 conforming to IEC 60529
Ik Degree Of Protection	IK08 conforming to IEC 62262

Packing Units

-	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	12.600 cm
Package 1 Width	16.600 cm
Package 1 Length	13.600 cm
Package 1 Weight	668.000 g
Unit Type Of Package 2	P12
Number Of Units In Package 2	144
Package 2 Height	80.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	113.000 kg

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Eu Rohs Directive	Compliant EU RoHS Declaration
Reach Regulation	REACh Declaration
Halogen Free Product	
Rohs Exemption Information	Yes
Mercury Free	
Toxic Heavy Metal Free	
Reach Free Of Svhc	