# **Product datasheet**





## Auxiliary contact block, TeSys D, 1NO + 1NC, side mounting, screw clamp terminals

LAD8N11

Local distributor code: 381799386

EAN Code: 3389110384673

#### Main

IVIAIII	
Range	TeSys
Product Name	TeSys Deca
Product Or Component Type	Auxiliary contact block
Range Compatibility	TeSys Deca LC1D0995 AC coil TeSys Deca LC1D115/150 TeSys Deca LC1D40A80A AC Coil TeSys Deca CAD AC coil TeSys F LC1F
Mounting Location	Side
Pole Contact Composition	1 NO + 1 NC
Contacts Operation	Instantaneous
[Ue] Rated Operational Voltage	690 V AC 25400 Hz
[le] Rated Operational Current	6 A at 120 V AC-15 1.04 A at 690 V AC-15 0.55 A at 125 V DC-13 0.1 A at 600 V DC-13
[Ui] Rated Insulation Voltage	690 V conforming to IEC 60947-5-1 600 V conforming to UL 600 V conforming to CSA
[Ith] Conventional Free Air Thermal Current	10 A (at 60 °C)
Standards	UL 60947-5-1 CSA C22.2 No 60947-5-1 GB/T 14048.5 EN/IEC 60947-5-1
Product Certifications	CB UL CSA CCC EAC UKCA

### Complementary

Irms Rated Making Capacity	140 A AC conforming to IEC 60947-5-1 250 A DC conforming to IEC 60947-5-1
Permissible Short-Time Rating	100 A 1 s 120 A 500 ms 140 A 100 ms
Protection Type	GG fuse 10 A
Mechanical Durability	30 Mcycles
Minimum Switching Current	5 mA
Minimum Switching Voltage	17 V

Life Is On Schneider 19 Apr 2024

Non-Overlap Time	<ul><li>1.5 ms on de-energisation no overlap between NC and NO contact</li><li>1.5 ms on energisation no overlap between NC and NO contact</li></ul>	
Insulation Resistance	> 10 MOhm	
Connections - Terminals	Screw clamp terminals 1 cable(s) 14 mm²flexible with cable end Screw clamp terminals 1 cable(s) 14 mm²flexible without cable end Screw clamp terminals 2 cable(s) 12.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 14 mm²flexible without cable end Screw clamp terminals 1 cable(s) 14 mm²flexible without cable end	
Tightening Torque	Screw clamp terminals 2 cable(s) 14 mm²rigid without cable end  1.7 N.m - with screwdriver flat Ø 6 mm	
	<ul><li>1.7 N.m - with screwdriver Philips No 2</li><li>1.7 N.m - with screwdriver pozidriv No 2</li></ul>	
Height	76 mm	
Width	12.5 mm	
Depth	76 mm	

### **Environment**

Environmental Characteristic	Normal environment
Ip Degree Of Protection	IP20 conforming to IEC 60529
Protective Treatment	TH conforming to IEC 60068
Ambient Air Temperature For Storage	-6080 °C
Ambient Air Temperature For Operation	-560 °C
Operating Altitude	3000 m

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.2 cm
Package 1 Width	7.1 cm
Package 1 Length	7.5 cm
Package 1 Weight	62.0 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	60
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	4.308 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	960
Package 3 Height	75 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	79 kg

# **Contractual warranty**

Warranty

18 months

### Sustainability Screen Premium\*

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>⊘</b>	Reach Free Of Svhc	
<b>⊘</b>	Toxic Heavy Metal Free	
<b>⊘</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations