Product datasheet

Specification





TeSys D contactor - 4P(4 NO) - AC-1 - <= 440 V 20 A - 110 V DC standard coil

Local distributor code: 386105137

LC1DT20FD

EAN Code: 3389110247787

Main

Range	TeSys TeSys Deca
Range Of Product	TeSys Deca
Product Or Component Type	Contactor
Device Short Name	LC1D
Contactor Application	Resistive load
Utilisation Category	AC-1
Poles Description	4P
[Ue] Rated Operational Voltage	Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC
[le] Rated Operational Current	20 A (at <60 °C) at <= 440 V AC AC-1 for power circuit
[Uc] Control Circuit Voltage	110 V DC

Complementary

Compatibility Code	LC1D
Pole Contact Composition	4 NO
Protective Cover	With
[Ith] Conventional Free Air Thermal Current	10 A (at 60 °C) for signalling circuit 20 A (at 60 °C) for power circuit
Irms Rated Making Capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 250 A at 440 V for power circuit conforming to IEC 60947
Rated Breaking Capacity	250 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand Current	30 A 40 °C - 10 min for power circuit 61 A 40 °C - 1 min for power circuit 105 A 40 °C - 10 s for power circuit 210 A 40 °C - 1 s for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 25 A gG at <= 690 V coordination type 1 for power circuit 20 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	2.5 mOhm - Ith 20 A 50 Hz for power circuit
Power Dissipation Per Pole	1.56 W AC-1

[Ui] Rated Insulation Voltage	Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Signalling circuit: 690 V conforming to IEC 60947-1 Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified Power circuit: 690 V conforming to IEC 60947-4-1
Overvoltage Category	III
Pollution Degree	3
[Uimp] Rated Impulse Withstand	6 kV conforming to IEC 60947
Voltage Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mechanical Durability	30 Mcycles
Control Circuit Type	DC standard
Coil Technology	Built-in bidirectional peak limiting diode suppressor
Control Circuit Voltage Limits	0.10.25 Uc (-4070 °C):drop-out DC 0.71.25 Uc (-4060 °C):operational DC 11.25 Uc (6070 °C):operational DC
Inrush Power In W	5.4 W (at 20 °C)
Hold-In Power Consumption In W	5.4 W at 20 °C
Operating Time	20 ±20 % ms opening 63 ±15 % ms closing
Time Constant	28 ms
Maximum Operating Rate	3600 cyc/h 60 °C
Connections - Terminals	Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid without cable end Power circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid without cable end Power circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid without cable end
Tightening Torque	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2 Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2
Auxiliary Contact Composition	1 NO + 1 NC
Auxiliary Contacts Type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1
Signalling Circuit Frequency	25400 Hz
Minimum Switching Voltage	17 V for signalling circuit
Minimum Switching Current	5 mA for signalling circuit

Non-Overlap Time 1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact Rail Plate Environment Standards CSA C22.2 No 14 EN 60947-4-1 EN 60947-4-1 EN 60947-4-1 EN 60947-5-1 UL 508 EN UL CSC GL EROS (Lloyds register of shipping) RINA CSA Protective Treatment TH conforming to IEC 605829 Protective Treatment TH conforming to IEC 60947-1 Annex Q category D exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-		
Non-Overlap Time 1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact Rail Plate Environment Standards CSA C22.2 No 14 EN 60947-4-1 IEC 60947-4-1 IEC 60947-4-1 IEC 60947-8-1 UL 508 IEC 60335-1 Product Certifications DNV GOST BV UL CCC GL LROS (Lloyds register of shipping) RINA CSA LROS (Lloyds register of shipping) RINA CSA Up Degree Of Protection IP20 front face conforming to IEC 60529 Protective Treatment TH conforming to IEC 60068-2-30 Climatic Withstand conforming to IEC 60947-1 Annex Q category D exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat		
### The conforming to IEC 605829 Protective Treatment The conforming to IEC 60589 The conforming to IEC 60947-1 Annex Q category D exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat conforming to IEC 6058-2-1 U. 60° C 6070° C with derating D3000 m C3000 Hz) Vibrations contactor closed (4 Gn, 53000 Hz) Vibrations contactor closed (15 Gn for 11 ms) Vibrations c	Insulation Resistance	> 10 MOhm for signalling circuit
Environment Standards CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 609347-5-1 IEC 609347-5-1 IEC 609347-5-1 UL 508 IEC 60335-1 Product Certifications DNV GOST BV UL CCC GL LROS (Lloyds register of shipping) RINA CSA Ip Degree Of Protection IP20 front face conforming to IEC 60529 Protective Treatment TH conforming to IEC 60068-2-30 Climatic Withstand conforming to IEC 60068-2-30 Climatic Withstand conforming to IEC 60947-1 Annex Q category D exposure to damp heat conforming to IEC 60047-1 Annex Q category D exposure to damp heat Permissible Ambient Air Temperature Around The Device 4060 °C 6070 °C with derating Operating Altitude 03000 m Fire Resistance 850 °C conforming to IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open (2 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms)	Non-Overlap Time	· · · · · · · · · · · · · · · · · · ·
Standards CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-5-1 IEC 60947-5-1 UL 508 IEC 60335-1 Product Certifications DNV GOST BV UL CCC GL LROS (Lloyds register of shipping) RINA CSA Ip Degree Of Protection IP20 front face conforming to IEC 60529 Protective Treatment TH conforming to IEC 60068-2-30 Climatic Withstand conforming to IACS E10 exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Conforming	Mounting Support	
EN 60947-4-1 EN 60947-5-1 IEC 60947-5-1 IEC 60947-5-1 UL 508 IEC 60335-1 Product Certifications DNV GOST BV UL CCC GL LROS (Lloyds register of shipping) RINA CSA Protective Treatment TH conforming to IEC 60068-2-30 Climatic Withstand conforming to IEC 60068-2-30 Climatic Withstand conforming to IEC 60947-1 Annex Q category D exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat conforming to IEC 60947-1 Special Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Special Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to IEC 60947-1 Annex Q category D exposure to damp heat Conforming to	Environment	
GOST BV UL CCC GL LROS (Lloyds register of shipping) RINA CSA Ip Degree Of Protection IP20 front face conforming to IEC 60529 Protective Treatment TH conforming to IEC 60068-2-30 Climatic Withstand conforming to IACS E10 exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat Permissible Ambient Air Temperature Around The Device 6070 °C with derating Operating Altitude 03000 m Fire Resistance 850 °C conforming to IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms)	Standards	EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508
Protective Treatment TH conforming to IEC 60068-2-30 Climatic Withstand conforming to IACS E10 exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat Permissible Ambient Air	Product Certifications	GOST BV UL CCC GL LROS (Lloyds register of shipping) RINA
Climatic Withstand conforming to IACS E10 exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat -4060 °C 6070 °C with derating Operating Altitude 03000 m Fire Resistance 850 °C conforming to IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms)	Ip Degree Of Protection	IP20 front face conforming to IEC 60529
conforming to IEC 60947-1 Annex Q category D exposure to damp heat Permissible Ambient Air Temperature Around The Device 6070 °C with derating Operating Altitude 03000 m Fire Resistance 850 °C conforming to IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms)	Protective Treatment	TH conforming to IEC 60068-2-30
Temperature Around The Device 6070 °C with derating Operating Altitude 03000 m Fire Resistance 850 °C conforming to IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms)	Climatic Withstand	
Fire Resistance 850 °C conforming to IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms)		
Flame Retardance V1 conforming to UL 94 Mechanical Robustness Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms)	Operating Altitude	03000 m
Mechanical Robustness Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms)	Fire Resistance	850 °C conforming to IEC 60695-2-1
Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms)	Flame Retardance	V1 conforming to UL 94
<u> </u>	Mechanical Robustness	Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms)

Packing Units

Height

Width

Depth

Net Weight

_	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.842 cm
Package 1 Width	9.652 cm
Package 1 Length	12.192 cm
Package 1 Weight	521.637 g

85 mm

45 mm

99 mm

0.365 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes
⊘	Pvc Free	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information