Product datasheet

Specifications





TeSys D contactor - 4P(4 NO) -AC-1 - <= 440 V 25 A - 220 V AC 50/60 Hz coil

Local distributor code: 386105292

LC1DT25M7

EAN Code: 3389110577679

Main

| Range | TeSys TeSys Deca |
|--------------------------------|---|
| Range Of Product | TeSys Deca |
| Product Or Component Type | Contactor |
| Device Short Name | LC1D |
| Contactor Application | Resistive load |
| Utilisation Category | AC-1 AC-3 AC-3e AC-4 |
| Poles Description | 4P |
| [Ue] Rated Operational Voltage | Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC |
| [le] Rated Operational Current | 25 A (at <60 °C) at <= 440 V AC AC-1 for power circuit |
| [Uc] Control Circuit Voltage | 220 V AC 50/60 Hz |

Complementary

| <u> </u> | |
|--|--|
| Compatibility Code | LC1D |
| Pole Contact Composition | 4 NO |
| Protective Cover | With |
| [Ith] Conventional Free Air Thermal Current | 10 A (at 60 °C) for signalling circuit 25 A (at 60 °C) for power circuit |
| Irms Rated Making Capacity | 140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 250 A at 440 V for power circuit conforming to IEC 60947 |
| Rated Breaking Capacity | 250 A at 440 V for power circuit conforming to IEC 60947 |
| [Icw] Rated Short-Time Withstand Current | 30 A 40 °C - 10 min for power circuit 61 A 40 °C - 1 min for power circuit 105 A 40 °C - 10 s for power circuit 210 A 40 °C - 1 s for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit |
| Associated Fuse Rating | 10 A gG for signalling circuit conforming to IEC 60947-5-1 40 A gG at <= 690 V coordination type 1 for power circuit 25 A gG at <= 690 V coordination type 2 for power circuit |
| Average Impedance | 2.5 mOhm - Ith 25 A 50 Hz for power circuit |
| Power Dissipation Per Pole | 1.56 W AC-1 |

| [Ui] Rated Insulation Voltage | Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Signalling circuit: 690 V conforming to IEC 60947-1 Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified Power circuit: 690 V conforming to IEC 60947-4-1 |
|---|---|
| Overvoltage Category | III |
| Pollution Degree | 3 |
| [Uimp] Rated Impulse Withstand Voltage | 6 kV conforming to IEC 60947 |
| Safety Reliability Level | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 |
| Mechanical Durability | 15 Mcycles |
| Electrical Durability | 0.8 Mcycles 25 A AC-1 at Ue <= 440 V |
| Control Circuit Type | AC at 50/60 Hz |
| Coil Technology | Without built-in suppressor module |
| Control Circuit Voltage Limits | 0.30.6 Uc (-4070 °C):drop-out AC 50/60 Hz 0.81.1 Uc (-4060 °C):operational AC 50 Hz 0.851.1 Uc (-4060 °C):operational AC 60 Hz 11.1 Uc (6070 °C):operational AC 50/60 Hz |
| Inrush Power In Va | 70 VA 60 Hz cos phi 0.75 (at 20 °C) 70 VA 50 Hz cos phi 0.75 (at 20 °C) |
| Hold-In Power Consumption In Va | 7.5 VA 60 Hz cos phi 0.3 (at 20 °C) 7 VA 50 Hz cos phi 0.3 (at 20 °C) |
| Heat Dissipation | 23 W at 50/60 Hz |
| Operating Time | 419 ms opening 1222 ms closing |
| Maximum Operating Rate | 3600 cyc/h 60 °C |
| Connections - Terminals | Control circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 14 mm ² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 14 mm ² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 14 mm ² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 14 mm ² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 14 mm ² - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 1 14 mm ² - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 1 14 mm ² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 14 mm ² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: solid without cable end Power circuit: screw clamp terminals 1 14 mm ² - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 12.4 mm ² - cable stiffness: solid without cable end |
| Tightening Torque | Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2 Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2 |
| Auxiliary Contact Composition | 1 NO + 1 NC |
| Auxiliary Contacts Type | type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1 |

| Signalling Circuit Frequency | 25400 Hz |
|------------------------------|---|
| Minimum Switching Voltage | 17 V for signalling circuit |
| Minimum Switching Current | 5 mA for signalling circuit |
| Insulation Resistance | > 10 MOhm for signalling circuit |
| Non-Overlap Time | 1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact |
| Mounting Support | Plate Rail |

Environment

| Standards | CSA C22.2 No 14 |
|-------------------------------|--|
| | EN 60947-4-1 |
| | EN 60947-5-1 |
| | IEC 60947-4-1 |
| | IEC 60947-5-1 |
| | |
| | UL 508 |
| | IEC 60335-1 |
| Product Certifications | GOST |
| | DNV |
| | LROS (Lloyds register of shipping) |
| | CSA |
| | UL |
| | RINA |
| | |
| | BV |
| | GL |
| | CCC |
| Ip Degree Of Protection | IP20 front face conforming to IEC 60529 |
| Protective Treatment | TH conforming to IEC 60068-2-30 |
| Climatic Withstand | conforming to IACS E10 exposure to damp heat |
| | conforming to IEC 60947-1 Annex Q category D exposure to damp heat |
| Permissible Ambient Air | -4060 °C |
| Temperature Around The Device | 6070 °C with derating |
| | |
| Operating Altitude | 03000 m |
| Fire Resistance | 850 °C conforming to IEC 60695-2-1 |
| Flame Retardance | V1 conforming to UL 94 |
| Mechanical Robustness | Vibrations contactor open (2 Gn, 5300 Hz) |
| | Vibrations contactor closed (4 Gn, 5300 Hz) |
| | Shocks contactor closed (15 Gn for 11 ms) |
| | Shocks contactor open (10 Gn for 11 ms) |
| | |
| Height | 85 mm |
| Width | 45 mm |
| Depth | 92 mm |
| Net Weight | 0.365 kg |
| | |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 5.500 cm |
| Package 1 Width | 9.500 cm |
| Package 1 Length | 11.800 cm |
| Package 1 Weight | 390.000 g |

| Unit Type Of Package 2 | S02 |
|------------------------------|-----------|
| Number Of Units In Package 2 | 16 |
| Package 2 Height | 15.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 6.716 kg |

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|--|
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | End of Life Information |