Product datasheet

Specifications





REVERSING CONTACTOR 575VAC 25A IEC

LC2DT25F7

EAN Code: 3389110515442

Main

Range	TeSys
Product Name	TeSys D
Product Or Component Type	Changeover contactor
Device Short Name	LC2D
Contactor Application	Resistive load
Utilisation Category	AC-1
Device Presentation	Preassembled, with prewired power connections
Poles Description	4P
Power Pole Contact Composition	4 NO
[Ue] Rated Operational Voltage	Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC
[Ie] Rated Operational Current	25 A (at <60 °C) at <= 440 V AC AC-1 for power circuit
Control Circuit Type	AC at 50/60 Hz
[Uc] Control Circuit Voltage	110 V AC 50/60 Hz
Auxiliary Contact Composition	1 NO + 1 NC
[Uimp] Rated Impulse Withstand Voltage	6 kV conforming to IEC 60947
Overvoltage Category	III
[Ith] Conventional Free Air Thermal Current	10 A (at 60 °C) for signalling circuit 25 A (at 60 °C) for power circuit
Irms Rated Making Capacity	250 A at 440 V for power circuit conforming to IEC 60947 140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1
Rated Breaking Capacity	250 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand Current	30 A 40 °C - 10 min for power circuit 61 A 40 °C - 1 min for power circuit 105 A 40 °C - 10 s for power circuit 210 A 40 °C - 1 s for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 40 A gG at <= 690 V coordination type 1 for power circuit 25 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	2.5 mOhm - Ith 25 A 50 Hz for power circuit

Power circuit: 690 V conforming to IEC 60947-4-1
Power circuit: 600 V CSA certified
Power circuit: 600 V UL certified
Signalling circuit: 690 V conforming to IEC 60947-1
Signalling circuit: 600 V CSA certified
Signalling circuit: 600 V UL certified
0.8 Mcycles 25 A AC-1 at Ue <= 690 V
1.56 W AC-1
With
Mechanical
Rail
Plate
CSA C22.2 No 60947-4-1
EN 60947-4-1
EN 60947-5-1
IEC 60947-4-1
IEC 60947-5-1
UL 60947-4-1
UL 60947-5-1
CSA C22.2 No 60947-5-1
GB/T 14048.4
UL
CSA
RINA
GOST
CCC
DNV
LROS (Lloyds register of shipping)
GL
BV
UKCA
СВ
Power circuit: screw clamp terminals 1 cable(s) 14 mm²flexible without cable end
Power circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end
Power circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible with cable end
· · · · · · · · · · · · · · · · · · ·
Power circuit: screw clamp terminals 2 cable(s) 1 2 5 mm ² flexible with cable end
Power circuit: screw clamp terminals 2 cable(s) 12.5 mm ² flexible with cable end Power circuit: screw clamp terminals 1 cable(s) 14 mm ² solid
Power circuit: screw clamp terminals 1 cable(s) 14 mm ² solid
Power circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Power circuit: screw clamp terminals 2 cable(s) 14 mm ² solid
Power circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Power circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible without cable end
Power circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Power circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end
Power circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Power circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible without cable end
Power circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Power circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 12.5 mm ² flexible with cable end
Power circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Power circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 12.5 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 12.5 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm ² solid
Power circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Power circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 12.5 mm ² flexible with cable end
Power circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Power circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 12.5 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 12.5 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm ² solid
Power circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Power circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 12 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 12 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 12 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² solid
Power circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Power circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 12 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 12 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm
Power circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Power circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 12 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2
Power circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Power circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm
Power circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Power circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2
Power circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Power circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 1222 ms closing
Power circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Power circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 12 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 2 1222 ms closing 419 ms opening
Power circuit: screw clamp terminals 1 cable(s) 14 mm ² solid Power circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 125 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: screw clamp terminals 2 cable(s) 14 mm ² solid Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 1222 ms closing 419 ms opening B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1
Power circuit: screw clamp terminals 1 cable(s) 14 mm²solid Power circuit: screw clamp terminals 2 cable(s) 14 mm²solid Control circuit: screw clamp terminals 2 cable(s) 14 mm²flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm²flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm²flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm²flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm²flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm²flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm²flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm²solid Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 1222 ms closing 419 ms opening B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO
Power circuit: screw clamp terminals 1 cable(s) 14 mm²solid Power circuit: screw clamp terminals 2 cable(s) 14 mm²solid Control circuit: screw clamp terminals 2 cable(s) 14 mm²flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm²flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm²flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm²flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm²flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm²flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm²flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm²solid Control circuit: screw clamp terminals 2 cable(s) 14 mm²solid Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 1222 ms closing 419 ms opening B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1

Complementary

Control Circuit Voltage Limits 0.30.6 Uc (-4060 °C):drop-out AC 50/60 H 0.81.1 Uc (-4060 °C):operational AC 50 H 0.851.1 Uc (-4060 °C):operational AC 60 H	:

Inrush Power In Va	70 VA 60 Hz cos phi 0.75 (at 20 °C)
	70 VA 50 Hz cos phi 0.75 (at 20 °C)
Hold-In Power Consumption In Va	7.5 VA 60 Hz cos phi 0.3 (at 20 °C)
	7 VA 50 Hz cos phi 0.3 (at 20 °C)
Heat Dissipation	23 W at 50/60 Hz
Auxiliary Contacts Type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1
	type mirror contact 1 NC conforming to IEC 60947-4-1
Signalling Circuit Frequency	25400 Hz
Minimum Switching Current	5 mA for signalling circuit
Minimum Switching Voltage	17 V for signalling circuit
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact
	1.5 ms on energisation between NC and NO contact
Insulation Resistance	> 10 MOhm for signalling circuit

Environment

IP20 front face conforming to IEC 60529
conforming to IACS E10 conforming to IEC 60947-1 Annex Q category D
TH conforming to IEC 60068-2-30
3
-4060 °C 6070 °C with derating
-6080 °C
03000 m
850 °C conforming to IEC 60695-2-1
V1 conforming to UL 94
Vibrations contactor open: 2 Gn, 5300 Hz Vibrations contactor closed: 4 Gn, 5300 Hz Shocks contactor open: 10 Gn for 11 ms Shocks contactor closed: 15 Gn for 11 ms
85 mm
90 mm
90 mm
0.73 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.48 cm
Package 1 Width	9.0 cm
Package 1 Length	9.2 cm
Package 1 Weight	730.0 g

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information