# **Product datasheet**

Specifications





## TeSys D changeover contactor -4P(4 NO) - AC-1 - <= 440 V 25 A -230 V AC coil

Local distributor code: 389809498

LC2DT25P7

#### EAN Code: 3389110245233

#### Main

Range       TeSys Deca         Product Name       TeSys Deca         Product Or Component Type       Changeover contactor         Device Short Name       LC2D         Contactor Application       Resistive load         Utilisation Category       AC-1         Device Presentation       Preassembled, with prewired power connections         Poles Description       4P         Power Pole Contact Composition       4 NO         Util Rated Operational Voltage       Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC         [16] Rated Operational Current       25 A (at <60 °C) at <= 440 V AC AC-1 for power circuit         Control Circuit Type       AC at 50/60 Hz         Uvol Control Circuit Voltage       230 V AC 50/60 Hz         Auxiliary Contact Composition       1 NO + 1 NC         Util Control Circuit Voltage       230 V AC 50/60 Hz         Auxiliary Contact Composition       1 NO + 1 NC         Util Di Conventional Free Air       10 A (at 60 °C) for signalling circuit         25 A (at 440 V for power circuit       250 A 44 40 V for power circuit         Itrms Rated Making Capacity       250 A at 440 V for power circuit         Vortage       20 A 41 40 V for power circuit         Control Circuit Vithag       30 A 40 °C - 10 min for power circuit         <	mann	
TeSys Deca         Product Or Component Type       Changeover contactor         Device Short Name       LC2D         Contactor Application       Resistive load         Utilisation Category       AC-1         Device Presentation       Preassembled, with prewired power connections         Poles Description       4P         Power Pole Contact Composition       4 NO         (Ue] Rated Operational Voltage       Power circuit. <= 690 V AC 25400 Hz Power of Contact Composition         Power Pole Contact Composition       4 NO         (Ue] Rated Operational Voltage       Power circuit. <= 690 V AC 25400 Hz Power circuit         Power Control Corrent       25 A (at <60 °C) at <= 440 V AC AC-1 for power circuit	Range	•
Device Short Name         LC2D           Contactor Application         Resistive load           Utilisation Category         AC-1           Device Presentation         Preassembled, with prewired power connections           Poles Description         4P           Power Pole Contact Composition         4 NO           [Ue] Rated Operational Voltage         Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC	Product Name	•
Contactor Application       Resistive load         Utilisation Category       AC-1         Device Presentation       Preassembled, with prewired power connections         Poles Description       4P         Power Pole Contact Composition       4 NO         [Ue] Rated Operational Voltage       Power circuit: <= 600 V AC 25400 Hz Power circuit: <= 300 V DC	Product Or Component Type	Changeover contactor
Utilisation Category       AC-1         Device Presentation       Preassembled, with prewired power connections         Poles Description       4P         Power Pole Contact Composition       4 NO         [Ue] Rated Operational Voltage       Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 000 V DC	Device Short Name	LC2D
Device Presentation       Preassembled, with prewired power connections         Poles Description       4P         Power Pole Contact Composition       4 NO         [Ue] Rated Operational Voltage       Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC	Contactor Application	Resistive load
Poles Description       4P         Power Pole Contact Composition       4 NO         [Ue] Rated Operational Voltage       Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC	Utilisation Category	AC-1
Power Pole Contact Composition       4 NO         [Ue] Rated Operational Voltage       Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC	Device Presentation	Preassembled, with prewired power connections
[Ue] Rated Operational Voltage       Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC	Poles Description	4P
Power circuit: <= 300 V DC	Power Pole Contact Composition	4 NO
Control Circuit Type       AC at 50/60 Hz         [Uc] Control Circuit Voltage       230 V AC 50/60 Hz         Auxiliary Contact Composition       1 NO + 1 NC         [Uimp] Rated Impulse Withstand       6 kV conforming to IEC 60947         Voltage       0vervoltage Category         III       10 A (at 60 °C) for signalling circuit         25 A (at 60 °C) for power circuit       10 A (at 60 °C) for signalling circuit         Irms Rated Making Capacity       250 A at 440 V for power circuit conforming to IEC 60947         140 A AC for signalling circuit conforming to IEC 60947       140 A AC for signalling circuit conforming to IEC 60947-5-1         250 A DC for signalling circuit conforming to IEC 60947       100 A (at 40 °C - 10 min for power circuit         (current       30 A 40 °C - 10 min for power circuit         10 A 4 °C - 1 s for power circuit       210 A 40 °C - 1 s for power circuit         100 A - 15 for signalling circuit       120 A - 100 m for signalling circuit         120 A - 00 m s for signalling circuit       120 A - 100 m s for signalling circuit         120 A - 10 for power circuit       100 A - 1 s for power circuit         100 A - 1 s for signalling circuit       120 A - 0°C - 1 s for power circuit         100 A - 100 m s for signalling circuit       120 A - 0°C - 1 s for power circuit         120 A - 00 m s for signalling circuit       140 A - 100 m s for signallin	[Ue] Rated Operational Voltage	
[Uc] Control Circuit Voltage       230 V AC 50/60 Hz         Auxiliary Contact Composition       1 NO + 1 NC         [Uimp] Rated Impulse Withstand       6 kV conforming to IEC 60947         Overvoltage Category       III         [Ith] Conventional Free Air Thermal Current       10 A (at 60 °C) for signalling circuit 25 A (at 60 °C) for power circuit conforming to IEC 60947         Irms Rated Making Capacity       250 A at 440 V for power circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1         Rated Breaking Capacity       250 A at 440 V for power circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947         [Icw] Rated Short-Time Withstand Current       30 A 40 °C - 10 min for power circuit 105 A 40 °C - 10 s for power circuit 105 A 40 °C - 1 s for power circuit 105 A 40 °C - 1 s for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit 140 A - 100 ms for signalling circuit 140 A g G at <= 690 V coordination type 1 for power circuit 25 A g G at <= 690 V coordination type 2 for power circuit	[Ie] Rated Operational Current	25 A (at <60 °C) at <= 440 V AC AC-1 for power circuit
Auxilliary Contact Composition       1 NO + 1 NC         Auxilliary Contact Composition       1 NO + 1 NC         [Uimp] Rated Impulse Withstand       6 kV conforming to IEC 60947         Overvoltage Category       III         [Ith] Conventional Free Air       10 A (at 60 °C) for signalling circuit         Thermal Current       250 A at 440 V for power circuit         Irms Rated Making Capacity       250 A at 440 V for power circuit conforming to IEC 60947         140 A AC for signalling circuit conforming to IEC 60947-5-1         250 A DC for signalling circuit conforming to IEC 60947-5-1         250 A DC for signalling circuit conforming to IEC 60947         [Icw] Rated Short-Time Withstand       30 A 40 °C - 10 min for power circuit         Current       30 A 40 °C - 10 min for power circuit         10 A 40 °C - 1 min for power circuit       10 A 40 °C - 1 s for power circuit         10 A 40 °C - 1 s for power circuit       10 A 40 °C - 1 s for power circuit         10 A 40 °C - 1 s for signalling circuit       10 A - 1 s for signalling circuit         120 A - 500 ms for signalling circuit       10 A - 1 s for signalling circuit         140 A - 100 ms for signalling circuit       140 A - 100 ms for signalling circuit         140 A - 100 ms for signalling circuit       10 A g G at <= 690 V coordination type 1 for power circuit	Control Circuit Type	AC at 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage       6 kV conforming to IEC 60947         Overvoltage Category       III         [Ith] Conventional Free Air Thermal Current       10 A (at 60 °C) for signalling circuit 25 A (at 60 °C) for power circuit         Irms Rated Making Capacity       250 A at 440 V for power circuit conforming to IEC 60947 140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1         Rated Breaking Capacity       250 A at 440 V for power circuit conforming to IEC 60947         [Icw] Rated Short-Time Withstand Current       30 A 40 °C - 10 min for power circuit 61 A 40 °C - 10 s for power circuit 105 A 40 °C - 1 s for power circuit 210 A 40 °C - 1 s for signalling circuit 100 A - 1 s for signalling circuit 140 A - 100 ms for signalling circuit         Associated Fuse Rating       10 A gG for signalling circuit conforming to IEC 60947-5-1 40 A gG at <= 690 V coordination type 1 for power circuit 25 A gG at <= 690 V coordination type 2 for power circuit	[Uc] Control Circuit Voltage	230 V AC 50/60 Hz
Voltage       III         Overvoltage Category       III         [Ith] Conventional Free Air       10 A (at 60 °C) for signalling circuit         Thermal Current       25 A (at 60 °C) for power circuit         Irms Rated Making Capacity       250 A at 440 V for power circuit conforming to IEC 60947         Idt A AC for signalling circuit conforming to IEC 60947-5-1       250 A DC for signalling circuit conforming to IEC 60947-5-1         Rated Breaking Capacity       250 A at 440 V for power circuit conforming to IEC 60947         [Icw] Rated Short-Time Withstand       30 A 40 °C - 10 min for power circuit         Current       30 A 40 °C - 10 min for power circuit         105 A 40 °C - 1 min for power circuit       105 A 40 °C - 1 or signalling circuit         100 A - 1 s for power circuit       100 A - 1 s for signalling circuit         100 A - 1 s for signalling circuit       100 A - 1 s for signalling circuit         100 A - 1 s for signalling circuit       100 A - 1 s for signalling circuit         100 A = 60 w for signalling circuit       100 A gG at <= 690 V coordination type 1 for power circuit	Auxiliary Contact Composition	1 NO + 1 NC
[Ith] Conventional Free Air Thermal Current       10 A (at 60 °C) for signalling circuit 25 A (at 60 °C) for power circuit         Irms Rated Making Capacity       250 A at 440 V for power circuit conforming to IEC 60947 140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1         Rated Breaking Capacity       250 A at 440 V for power circuit conforming to IEC 60947         [Icw] Rated Short-Time Withstand       30 A 40 °C - 10 min for power circuit 61 A 40 °C - 10 min for power circuit 105 A 40 °C - 10 s for power circuit 210 A 40 °C - 1 s for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit         Associated Fuse Rating       10 A gG for signalling circuit conforming to IEC 60947-5-1 40 A gG at <= 690 V coordination type 1 for power circuit 25 A gG at <= 690 V coordination type 2 for power circuit		6 kV conforming to IEC 60947
Thermal Current       25 A (at 60 °C) for power circuit         Irms Rated Making Capacity       250 A at 440 V for power circuit conforming to IEC 60947 140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1         Rated Breaking Capacity       250 A at 440 V for power circuit conforming to IEC 60947         [Icw] Rated Short-Time Withstand       30 A 40 °C - 10 min for power circuit 61 A 40 °C - 1 min for power circuit 105 A 40 °C - 10 s for power circuit 210 A 40 °C - 1 s for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit         Associated Fuse Rating       10 A gG for signalling circuit conforming to IEC 60947-5-1 40 A gG at <= 690 V coordination type 1 for power circuit	Overvoltage Category	III
140 A AC for signalling circuit conforming to IEC 60947-5-1         250 A DC for signalling circuit conforming to IEC 60947-5-1         Rated Breaking Capacity       250 A at 440 V for power circuit conforming to IEC 60947         [lcw] Rated Short-Time Withstand       30 A 40 °C - 10 min for power circuit         61 A 40 °C - 1 min for power circuit       61 A 40 °C - 10 s for power circuit         210 A 40 °C - 10 s for power circuit       100 A - 1 s for signalling circuit         20 A - 1 s for signalling circuit       100 A - 1 s for signalling circuit         140 A - 100 ms for signalling circuit       100 A - 100 ms for signalling circuit         Associated Fuse Rating       10 A gG for signalling circuit conforming to IEC 60947-5-1         40 G at <= 690 V coordination type 1 for power circuit		
[Icw] Rated Short-Time Withstand       30 A 40 °C - 10 min for power circuit         61 A 40 °C - 1 min for power circuit       105 A 40 °C - 10 s for power circuit         105 A 40 °C - 1 s for power circuit       210 A 40 °C - 1 s for power circuit         210 A 40 °C - 1 s for power circuit       210 A 40 °C - 1 s for signalling circuit         100 A - 1 s for signalling circuit       120 A - 500 ms for signalling circuit         140 A - 100 ms for signalling circuit       140 A - 100 ms for signalling circuit         Associated Fuse Rating       10 A gG for signalling circuit conforming to IEC 60947-5-1         40 A gG at <= 690 V coordination type 1 for power circuit	Irms Rated Making Capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1
Current       61 A 40 °C - 1 min for power circuit         105 A 40 °C - 10 s for power circuit         210 A 40 °C - 1 s for power circuit         100 A - 1 s for signalling circuit         120 A - 500 ms for signalling circuit         140 A - 100 ms for signalling circuit         104 A - 100 ms for signalling circuit         Associated Fuse Rating         10 A gG for signalling circuit conforming to IEC 60947-5-1         40 A gG at <= 690 V coordination type 1 for power circuit	Rated Breaking Capacity	250 A at 440 V for power circuit conforming to IEC 60947
40 A gG at <= 690 V coordination type 1 for power circuit 25 A gG at <= 690 V coordination type 2 for power circuit		61 A 40 °C - 1 min for power circuit 105 A 40 °C - 10 s for power circuit 210 A 40 °C - 1 s for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit
Average Impedance       2.5 mOhm - Ith 25 A 50 Hz for power circuit	Associated Fuse Rating	40 A gG at <= 690 V coordination type 1 for power circuit
	Average Impedance	2.5 mOhm - Ith 25 A 50 Hz for power circuit

[Ui] Rated Insulation Voltage	Power circuit: 690 V conforming to IEC 60947-4-1
	Power circuit: 600 V CSA certified
	Power circuit: 600 V UL certified
	Signalling circuit: 690 V conforming to IEC 60947-1 Signalling circuit: 600 V CSA certified
	Signalling circuit: 600 V UL certified
Electrical Durability	0.8 Mcycles 25 A AC-1 at Ue <= 690 V
Power Dissipation Per Pole	1.56 W AC-1
Front Cover	With
Interlocking Type	Mechanical
Mounting Support	Rail Plate
Standards	CSA C22.2 No 60947-4-1
	EN 60947-4-1
	EN 60947-5-1
	IEC 60947-4-1
	IEC 60947-5-1
	UL 60947-4-1 UL 60947-5-1
	CSA C22.2 No 60947-5-1
	GB/T 14048.4
Product Certifications	UL
	CSA
	RINA
	GOST
	CCC
	DNV LROS (Lloyds register of shipping)
	GL
	BV
	UKCA
	СВ
Connections - Terminals	Power circuit: screw clamp terminals 1 cable(s) 14 mm <sup>2</sup> flexible without cable end
	Power circuit: screw clamp terminals 2 cable(s) 14 mm <sup>2</sup> flexible without cable end
	Power circuit: screw clamp terminals 1 cable(s) 14 mm <sup>2</sup> flexible with cable end
	Power circuit: screw clamp terminals 2 cable(s) 12.5 mm <sup>2</sup> flexible with cable end
	Power circuit: screw clamp terminals 1 cable(s) 14 mm <sup>2</sup> solid
	Power circuit: screw clamp terminals 2 cable(s) 14 mm <sup>2</sup> solid
	Control circuit: screw clamp terminals 1 cable(s) 14 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm <sup>2</sup> flexible without cable end
	Control circuit: screw clamp terminals 2 cable(s) 14 mm <sup>2</sup> flexible with cable end
	Control circuit: screw clamp terminals 2 cable(s) 12.5 mm <sup>2</sup> flexible with cable end
	Control circuit: screw clamp terminals 1 cable(s) 14 mm <sup>2</sup> solid
	Control circuit: screw clamp terminals 2 cable(s) 14 mm <sup>2</sup> solid
Fightening Torque	Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm
	Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2
	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm
	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2
	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2
	Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver pozidriv No 2
Operating Time	1222 ms closing 419 ms opening
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1
	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mechanical Durability	15 Mcycles
Mechanical Durability Maximum Operating Rate	

## Complementary

Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	0.30.6 Uc (-4060 °C):drop-out AC 50/60 Hz 0.81.1 Uc (-4060 °C):operational AC 50 Hz 0.851.1 Uc (-4060 °C):operational AC 60 Hz

Inrush Power In Va	70 VA 60 Hz cos phi 0.75 (at 20 °C)
	70 VA 50 Hz cos phi 0.75 (at 20 °C)
Hold-In Power Consumption In Va	7.5 VA 60 Hz cos phi 0.3 (at 20 °C)
	7 VA 50 Hz cos phi 0.3 (at 20 °C)
Heat Dissipation	23 W at 50/60 Hz
Auxiliary Contacts Type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1
	type mirror contact 1 NC conforming to IEC 60947-4-1
Signalling Circuit Frequency	25400 Hz
Minimum Switching Current	5 mA for signalling circuit
Minimum Switching Voltage	17 V for signalling circuit
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact
	1.5 ms on energisation between NC and NO contact
Insulation Resistance	> 10 MOhm for signalling circuit

## Environment

IP20 front face conforming to IEC 60529
conforming to IACS E10 conforming to IEC 60947-1 Annex Q category D
TH conforming to IEC 60068-2-30
3
-4060 °C 6070 °C with derating
-6080 °C
03000 m
850 °C conforming to IEC 60695-2-1
V1 conforming to UL 94
Vibrations contactor open: 2 Gn, 5300 Hz Vibrations contactor closed: 4 Gn, 5300 Hz Shocks contactor open: 10 Gn for 11 ms Shocks contactor closed: 15 Gn for 11 ms
85 mm
90 mm
90 mm
0.73 kg

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.500 cm
Package 1 Width	11.500 cm
Package 1 Length	14.200 cm
Package 1 Weight	850.000 g
Unit Type Of Package 2	\$02
Number Of Units In Package 2	5
Package 2 Height	15.000 cm

Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	4.578 kg

## **Contractual warranty**

Warranty

18 months

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

## Well-being performance

Reach Free Of Svhc
 Toxic Heavy Metal Free
 Mercury Free
 Rohs Exemption Information Yes
 Pvc Free

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information