Product datasheet





Compact NSXm-switch disconnector - 50A 3P - 1.28(Icm) 0.9(Icw) - compression lug

LV426650

! Discontinued on: 30 Jun 2023

! Discontinued

Important message: This product has been switched to new ComPacT range and is no longer commercialized.

EAN Code: 3606481176523

Main

| Range | ComPact |
|---------------------------|---------------------|
| Product Name | ComPact NSXm |
| Product Or Component Type | Switch disconnector |
| Device Application | Distribution |

Complementary

| [In] Rated Current | 50 A |
|---|--|
| Poles Description | 3P |
| Control Type | Toggle |
| Mounting Mode | Clip-on (35 mm symmetrical DIN rail) By screws (plate) |
| Network Type | AC |
| Network Frequency | 50/60 Hz |
| [le] Rated Operational Current | 50 A - utilisation category AC-23 AC 50/60 Hz 50 A - utilisation category AC-22 AC 50/60 Hz |
| [Ui] Rated Insulation Voltage | 800 V conforming to IEC 60947-2 |
| [Ue] Rated Operational Voltage | 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Icw] Rated Short-Time Withstand Current | 0.9 kA during 3 s conforming to IEC 60947-3 |
| [Icm] Rated Short-Circuit Making Capacity | 1.28 kA |
| [Uimp] Rated Impulse Withstand Voltage | 8 kV conforming to IEC 60947-2 |
| Suitability For Isolation | Yes conforming to IEC 60947-2 |
| Utilisation Category | Category A |
| Mechanical Durability | 20000 cycles conforming to IEC 947-1 Annex K ed 5.2 In |
| Electrical Durability | 10000 cycles conforming to IEC 947-1 Annex F ed 5.2 for In at 440 V |
| Contact Position Indicator | Yes |
| Connection Pitch | 27 mm 35 mm with spreaders |
| Local Signalling | Flag (green) for presence of auxiliary contacts |
| Toggle Padlocking (With Accessories) | Padlock in OFF or ON position |
| Connections - Terminals | compression lug/busbar |

Life Is On Schneider 25 Apr 2024

| Tightening Torque | 5 N.m for 2.510 mm ² 9 N.m for 1695 mm ² |
|-----------------------------|--|
| Thread Type | M6 |
| Number Of Slots | 1 slot(s) for auxiliary switch OF (plug-in) 1 slot(s) for alarm switch SD (plug-in) 1 slot(s) for voltage release MN or MX (plug-in) |
| Thickness | 8 mm |
| Power Wire Stripping Length | 20 mm |
| Quality Labels | CE |
| Standards | EN/IEC 60947 |
| Colour | Grey (RAL 7016) |
| Operating Altitude | 2000 m without derating 5000 m with derating |
| 9 Mm Pitches | 9 |
| Height | 137 mm |
| Width | 81 mm |
| Depth | 80 mm |
| Net Weight | 1.06 kg |
| Quantity Per Set | Set of 1 |

Environment

| Product Certifications | CCC EAC Marine |
|---------------------------------------|--|
| Ip Degree Of Protection | Front face: IP40 conforming to IEC 60529 |
| Ik Degree Of Protection | IK07 conforming to IEC 62262 |
| Pollution Degree | 3 conforming to IEC 60947-1 |
| Ambient Air Temperature For Operation | -2570 °C |
| Ambient Air Temperature For Storage | -5085 °C |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 9.0 cm |
| Package 1 Width | 12.5 cm |
| Package 1 Length | 22.0 cm |
| Package 1 Weight | 1.132 kg |

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

| Eu Rohs Directive | Compliant |
|-----------------------|---|
| | EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration |
| | Product out of China RoHS scope. Substance declaration for your information |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |