Product datasheet

Specifications





(!) Discontinued

circuit breaker ComPact NSX100N, 50 kA at 415 VAC, MicroLogic 2.2 trip unit 40 A, 4 poles 4d

LV429807

() Discontinued on: 15 Jun 2023

Important message: This product has been switched to new ComPacT range and is no longer commercialized. EAN Code: 3606480007576

Main

Range	ComPact
Product Name	ComPact NSX
Range Of Product	ComPact NSX100250
Device Short Name	NSX100N
Product Or Component Type	Circuit breaker
Device Application	Distribution
Number Of Poles	4P
Protected Poles Description	3t + N/2 4t 3t
Neutral Position	Left
[In] Rated Current	40 A at 40 °C
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz
Network Type	AC
Network Frequency	50/60 Hz
Suitability For Isolation	Yes conforming to EN/IEC 60947-2
Utilisation Category	Category A
[Icu] Rated Ultimate Short-Circuit Breaking Capacity	85 kA at 240 V AC 50/60 Hz conforming to UL 508 10 kA lcu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 35 kA lcu at 525 V AC 50/60 Hz conforming to IEC 60947-2 20 kA at 600 V AC 50/60 Hz conforming to UL 508 50 kA at 480 V AC 50/60 Hz conforming to UL 508 36 kA lcu at 500 V AC 50/60 Hz conforming to IEC 60947-2 50 kA lcu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 50 kA lcu at 440 V AC 50/60 Hz conforming to IEC 60947-2 90 kA lcu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2
Performance Level	N 50 KA 415 V AC
Trip Unit Name	MicroLogic 2.2
Trip Unit Technology	Electronic
Trip Unit Protection Functions	LSol
Control Type	Toggle
Circuit Breaker Mounting Mode	Fixed

Life Is On Schneider

Complementary

[Ui] Rated Insulation Voltage	800 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ics] Rated Service Short-Circuit Breaking Capacity	10 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 35 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2 36 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2 50 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 50 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 90 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2
Mechanical Durability	50000 cycles
Electrical Durability	10000 cycles at 690 V In 20000 cycles at 690 V In/2 30000 cycles at 440 V In 50000 cycles at 440 V In/2
Mounting Support	Backplate
Upside Connection	Front
Downside Connection	Front
Connection Pitch	35 mm
Protection Type	L : for overload protection (long time) So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection
Trip Unit Rating	40 A at 40 °C
Long-Time Pick-Up Adjustment Type Ir (Thermal Protection)	Adjustable 9 settings
[Ir] Long-Time Protection Pick-Up Adjustment Range	1840 A
Long-Time Protection Delay Adjustment Type Tr	Fixed
[Tr] Long-Time Protection Delay Adjustment Range	11 s at 7.2 x lr 16 s at 6 x lr 400 s at 1.5 x lr
	16 s at 6 x lr
Adjustment Range	16 s at 6 x Ir 400 s at 1.5 x Ir
Adjustment Range Thermal Memory Short-Time Protection Pick-Up	16 s at 6 x Ir 400 s at 1.5 x Ir 20 minutes before and after tripping
Adjustment Range Thermal Memory Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick-	16 s at 6 x Ir 400 s at 1.5 x Ir 20 minutes before and after tripping Adjustable 9 settings
Adjustment Range Thermal Memory Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick- Up Adjustment Range Short-Time Protection Delay	16 s at 6 x lr 400 s at 1.5 x lr 20 minutes before and after tripping Adjustable 9 settings 1.510 x lr
Adjustment Range Thermal Memory Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick- Up Adjustment Range Short-Time Protection Delay Adjustment Type Tsd Instantaneous Protection Pick-Up	16 s at 6 x lr 400 s at 1.5 x lr 20 minutes before and after tripping Adjustable 9 settings 1.510 x lr Fixed
Adjustment Range Thermal Memory Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick- Up Adjustment Range Short-Time Protection Delay Adjustment Type Tsd Instantaneous Protection Pick-Up Adjustment Type Ii [Ii] Instantaneous Protection Pick-	16 s at 6 x lr 400 s at 1.5 x lr 20 minutes before and after tripping Adjustable 9 settings 1.510 x lr Fixed Fixed
Adjustment Range Thermal Memory Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick- Up Adjustment Range Short-Time Protection Delay Adjustment Type Tsd Instantaneous Protection Pick-Up Adjustment Type Ii [Ii] Instantaneous Protection Pick- Up Adjustment Range	16 s at 6 x Ir 400 s at 1.5 x Ir 20 minutes before and after tripping Adjustable 9 settings 1.510 x Ir Fixed Fixed 600 A
Adjustment Range Thermal Memory Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick- Up Adjustment Range Short-Time Protection Delay Adjustment Type Tsd Instantaneous Protection Pick-Up Adjustment Type Ii [Ii] Instantaneous Protection Pick- Up Adjustment Range Earth-Leakage Protection	16 s at 6 x Ir 400 s at 1.5 x Ir 20 minutes before and after tripping Adjustable 9 settings 1.510 x Ir Fixed 600 A Without 0.5 x Ir (3t + N/2) 1 x Ir (4t)
Adjustment Range Thermal Memory Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick-Up Adjustment Range Short-Time Protection Delay Adjustment Type Tsd Instantaneous Protection Pick-Up Adjustment Type Ii [Ii] Instantaneous Protection Pick-Up Earth-Leakage Protection Neutral Protection Settings	16 s at 6 x Ir 400 s at 1.5 x Ir 20 minutes before and after tripping Adjustable 9 settings 1.510 x Ir Fixed 600 A Without 0.5 x Ir (3t + N/2) 1 x Ir (4t) No protection (3t)
Adjustment Range Thermal Memory Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick-Up Adjustment Range Short-Time Protection Delay Adjustment Type Tsd Instantaneous Protection Pick-Up Adjustment Type Ii [Ii] Instantaneous Protection Pick-Up Adjustment Range Earth-Leakage Protection Neutral Protection Settings Zone Selective Interlocking Zsi Number Of Slots For Electrical	16 s at 6 x Ir 400 s at 1.5 x Ir 20 minutes before and after tripping Adjustable 9 settings 1.510 x Ir Fixed 600 A Without 0.5 x Ir (3t + N/2) 1 x Ir (4t) No protection (3t) Without
Adjustment Range Thermal Memory Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick-Up Adjustment Range Short-Time Protection Delay Adjustment Type Tsd Instantaneous Protection Pick-Up Adjustment Type Ii [Ii] Instantaneous Protection Pick-Up Adjustment Range Earth-Leakage Protection Neutral Protection Settings Zone Selective Interlocking Zsi Number Of Slots For Electrical Auxiliaries	16 s at 6 x Ir 400 s at 1.5 x Ir 20 minutes before and after tripping Adjustable 9 settings 1.510 x Ir Fixed 600 A Without 0.5 x Ir (3t + N/2) 1 x Ir (4t) No protection (3t) Without 5 slot(s) Flashing LED (green) for ready to operate LED 105 % Ir (red) for overload
Adjustment Range Thermal Memory Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick-Up Adjustment Range Short-Time Protection Delay Adjustment Type Tsd Instantaneous Protection Pick-Up Adjustment Type Ii [Ii] Instantaneous Protection Pick-Up Adjustment Range Earth-Leakage Protection Neutral Protection Settings Zone Selective Interlocking Zsi Number Of Slots For Electrical Auxiliaries Local Signalling	16 s at 6 x lr 400 s at 1.5 x lr 20 minutes before and after tripping Adjustable 9 settings 1.510 x lr Fixed Fixed 600 A Without 0.5 x lr (3t + N/2) 1 x lr (4t) No protection (3t) Without 5 slot(s) Flashing LED (green) for ready to operate LED 105 % lr (red) for overload LED 90 % lr (orange) for overload
Adjustment Range Thermal Memory Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick-Up Adjustment Range Short-Time Protection Delay Adjustment Type Tsd Instantaneous Protection Pick-Up Adjustment Type Ii [Ii] Instantaneous Protection Pick-Up Adjustment Type Ii [Iii] Instantaneous Protection Pick-Up Adjustment Range Earth-Leakage Protection Neutral Protection Settings Zone Selective Interlocking Zsi Number Of Slots For Electrical Auxiliaries Local Signalling Width (W)	16 s at 6 x lr 400 s at 1.5 x lr 20 minutes before and after tripping Adjustable 9 settings 1.510 x lr Fixed 600 A Without 0.5 x lr (3t + N/2) 1 x lr (4t) No protection (3t) Without 5 slot(s) Flashing LED (green) for ready to operate LED 105 % lr (real) for overload LED 90 % lr (orange) for overload 140 mm

Environment

Standards	EN/IEC 60947
Product Certifications	CCC EAC Marine
Overvoltage Category	Class II
Electrical Shock Protection Class	Class II
Pollution Degree	3 conforming to IEC 60664-1
Ip Degree Of Protection	IP40 conforming to IEC 60529
Ik Degree Of Protection	IK07 conforming to IEC 62262
Ambient Air Temperature For Operation	-2570 °C
Ambient Air Temperature For Storage	-5085 °C
Relative Humidity	095 %
Operating Altitude	02000 m without derating 2000 m5000 m with derating

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	14.0 cm
Package 1 Width	14.5 cm
Package 1 Length	19.0 cm
Package 1 Weight	2.407 kg

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance



Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information