


# Product datasheet

Specifications



## TeSys F - specific contactor coil - 415...440V AC 40...400 Hz low consumption

Local distributor code:  
402992907

LX9FF415

⚠ Discontinued on: 29 Sept 2023

⚠ To be discontinued

EAN Code: 3389110083965

### Main

Range	TeSys
Product Or Component Type	Specific contactor coil
Device Short Name	LX9FF
Range Compatibility	TeSys TeSys F LC1F contactor
Product Compatibility	LC1F115 LC1F150
Control Circuit Type	AC at 40...400 Hz low consumption
[Uc] Control Circuit Voltage	415...440 V AC 40...400 Hz
Inductance Of Closed Circuit	30 H
Average Resistance	218 Ohm inrush at 20 °C 8460 Ohm holding at 20 °C
Operating Time	130 ms opening 35 ms closing
Mechanical Durability	10 Mcycles
Maximum Operating Rate	2400 cyc/h 55 °C

### Complementary

Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	Operational: 0.85...1.1 Uc (at 55 °C) Drop-out: 0.2...0.55 Uc (at 55 °C)
Inrush Power In Va	690...855 VA 40...400 Hz (at 20 °C)
Hold-In Power Consumption In Va	6.6...8.1 VA 40...400 Hz (at 20 °C)
Heat Dissipation	5.9...7.2 W

### Environment

Ambient Air Temperature For Operation	-5...55 °C
Net Weight	0.43 kg

### Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.6 cm
Package 1 Width	10.4 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Length	18.0 cm
Package 1 Weight	517.0 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	14
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	7.99 kg

## Contractual warranty

Warranty	18 months
----------	-----------

## Sustainability




**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

## Well-being performance

	Reach Free Of Svhc	
	Mercury Free	
	Rohs Exemption Information	Yes
Reach Regulation		<a href="#">REACH Declaration</a>
Eu Rohs Directive		Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation		<a href="#">China RoHS declaration</a>