# Product datasheet

Specifications

**Green Premium™**

## ClimaSys standard cooling unit side of enclosure - 2000W at 400 V

Local distributor code:
402654449                NSYCU2K3P4UL

⚠ **Discontinued on:** 9 Feb 2023

⚠ **Discontinued**

**EAN Code: 3606480653803**

## Main

| | |
|---|---|
| **Range** | ClimaSys |
| **Product Name** | CU |
| **Product Or Component Type** | Cooling unit |
| **Mounting Type** | Side |
| **Installation** | Indoor side |
| **Product Destination** | For enclosure |
| **Mounting Mode** | By screws |
| **Supply Voltage** | 460 V AC at 60 Hz, 3 phases |
| **Rated Power** | 2300 W |
| **Cooling Power** | 6820 Btu/h 60 Hz L35-L35<br>5150 Btu/h 60 Hz L35-L50 |

## Complementary

| | |
|---|---|
| **Height** | 999 mm |
| **Width** | 405 mm |
| **Depth** | 237 mm |
| **[In] Rated Current** | 2.5 A |
| **Inrush Current** | 10 A |
| **Power Consumption In W** | 970 W at 60 Hz, L35-L35<br>1150 W at 60 Hz, L35-L50 |
| **Energy Efficiency Ratio** | 2.1 |
| **Control Type** | Electronic controller |
| **Temperature Setting Range** | 20…45 °C |
| **Ambient Air Temperature For Operation** | 20…45 °C outside the enclosure:<br>45 °C maximum:<br>20…45 °C inside the enclosure: |
| **Noise Level** | 65 dB |
| **Pressure** | 25 bar |
| **Flow Rate** | External circuit: 1050 m3/h at 60 Hz<br>Internal circuit: 860 m3/h at 60 Hz |
| **Net Weight** | 54 kg |
| **Cooling Gas Type** | R134a (0.59 kg) |
| **Type Of Filter** | Optional external circuit filter |

| Protection Type | Thermal protection: T 6 A<br>Short-circuit protection (magnetic): |
|---|---|
| Material | Steel |
| Colour | Grey (RAL 7035) |

## Environment

| Product Certifications | UL |
|---|---|
| Standards | DIN 3168 |
| Ip Degree Of Protection | IP55 conforming to IEC 60529 (on the internal circuit)<br>IP34 conforming to IEC 60529 (on the external circuit) |

## Packing Units

| Unit Type Of Package 1 | PCE |
|---|---|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 23.7 cm |
| Package 1 Width | 40.5 cm |
| Package 1 Length | 99.9 cm |
| Package 1 Weight | 54.0 kg |
| Unit Type Of Package 2 | P12 |
| Number Of Units In Package 2 | 5 |
| Package 2 Height | 125.0 cm |
| Package 2 Width | 80.0 cm |
| Package 2 Length | 120.0 cm |
| Package 2 Weight | 342.0 kg |

## Contractual warranty

| Warranty | 18 months |
|---|---|

# Sustainability ![Green Premium™]

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-$CO_2$ products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium ›

Guide to assess a product's sustainability ›

Transparency    RoHS/REACh

## Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information       Yes

## Certifications & Standards

**Reach Regulation**

REACh Declaration

**Eu Rohs Directive**

Compliant

EU RoHS Declaration

**China Rohs Regulation**

China RoHS declaration

Pro-active China RoHS declaration (out of China RoHS legal scope)

**Environmental Disclosure**

Product Environmental Profile

**Weee**

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

**Circularity Profile**

End of Life Information