Product datasheet

Specification





ClimaSys standard cooling unit roof of enclosure - 2050W at 230 V

Local distributor code:

402654452 NSYCU2KR

- Discontinued on: 23 Nov 2023
- ! End-of-service on: 23 Feb 2024

① Discontinued

EAN Code: 3606480620959

Main

| Range | ClimaSys | |
|---------------------------|--|--|
| Product Name | CU | |
| Product Or Component Type | Cooling unit | |
| Mounting Type | Roof of enclosure | |
| Installation | Indoor roof | |
| Product Destination | For enclosure | |
| Mounting Mode | By screws | |
| Supply Voltage | 230 V AC at 50/60 Hz, 1 phase | |
| Rated Power | 2050 W | |
| Cooling Power | 2050 W 50/60 Hz L35-L35 1560 W 50/60 Hz L35-L50 | |

Complementary

| Height | 415 mm | |
|---------------------------------------|---|--|
| Width | 567 mm | |
| Depth | 401 mm | |
| [In] Rated Current | 6 A | |
| Inrush Current | 24 A | |
| Power Consumption In W | 1150 W at 50/60 Hz, L35-L35 1250 W at 50/60 Hz, L35-L50 | |
| Energy Efficiency Ratio | 1.8 | |
| Control Type | Electronic controller | |
| Temperature Setting Range | 2055 °C at 50 Hz 2050 °C at 60 Hz | |
| Ambient Air Temperature For Operation | 2046 °C inside the enclosure: 55 °C maximum: 2055 °C at 50 Hz outside the enclosure: 2050 °C at 60 Hz outside the enclosure: | |
| Noise Level | 65 dB conforming to EN/ISO 3746 | |
| Pressure | 25 bar | |
| Flow Rate | External circuit: 1820 m3/h at 50/60 Hz Internal circuit: 1050 m3/h at 50/60 Hz | |
| Net Weight | 50 kg | |
| | | |

| Cooling Gas Type | R134a (0.55 kg) | |
|------------------|---|--|
| Type Of Filter | Optional external circuit filter | |
| Protection Type | Thermal protection: T 10 A Short-circuit protection (magnetic): | |
| Material | Steel | |
| Colour | Grev (RAL 7035) | |

Environment

| Product Certifications | CE |
|-------------------------|---|
| Directives | 2006/95/EC - low voltage directive 2004/108/EC - electromagnetic compatibility 2006/42/EC - machinery |
| Standards | EN 60335-2-40 EN 60204-1 EN 378 EN/ISO 12100 EN 60335-1 |
| Ip Degree Of Protection | IP34 conforming to IEC 60529 (on the external circuit) IP54 conforming to IEC 60529 (on the internal circuit) |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 40.1 cm |
| Package 1 Width | 41.5 cm |
| Package 1 Length | 56.7 cm |
| Package 1 Weight | 50.0 kg |
| Unit Type Of Package 2 | P12 |
| Number Of Units In Package 2 | 2 |
| Package 2 Height | 68.0 cm |
| Package 2 Width | 80.0 cm |
| Package 2 Length | 120.0 cm |
| Package 2 Weight | 137.0 kg |

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| Ø | Reach Free Of Svhc | |
|----------|----------------------------|-----|
| ⊘ | Toxic Heavy Metal Free | |
| Ø | Mercury Free | |
| ⊘ | Rohs Exemption Information | Yes |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | End of Life Information |