# **Product datasheet**





! Discontinued

# ClimaSys std cooling unit on enclosure, in horizontal position -300W at 230 V

Local distributor code: 402654630

NSYCU300H

! Discontinued on: 23 Nov 2023

! End-of-service on: 23 Feb 2024

EAN Code: 3606480620768

#### Main

| Range                     | ClimaSys   |  |
|---------------------------|--|--|
| Product Name              | CU   |  |
| Product Or Component Type | Cooling unit                                     |  |
| Mounting Type             | On enclosure, in horizontal position<br>Side     |  |
| Installation              | Indoor side                                      |  |
| Product Destination       | For enclosure                                    |  |
| Supply Voltage            | 230 V AC at 50/60 Hz, 1 phase                    |  |
| Rated Power               | 300 W  |  |
| Cooling Power             | 300 W 50/60 Hz L35-L35<br>150 W 50/60 Hz L35-L50 |  |

### Complementary

| •                                     |   |
|---------------------------------------|---|
| Height                                | 340 mm  |
| Width                                 | 525 mm  |
| Depth                                 | 135 mm  |
| [In] Rated Current                    | 1.5 A   |
| Inrush Current                        | 4.2 A   |
| Power Consumption In W                | 270 W at 50/60 Hz, L35-L35<br>310 W at 50/60 Hz, L35-L50  |
| Energy Efficiency Ratio 1.1           |   |
| Control Type                          | Electronic controller   |
| Temperature Setting Range             | 2055 °C at 50 Hz<br>2050 °C at 60 Hz  |
| Ambient Air Temperature For Operation | 2046 °C inside the enclosure:<br>55 °C maximum:<br>2055 °C at 50 Hz outside the enclosure:<br>2050 °C at 60 Hz outside the enclosure: |
| Noise Level                           | 61 dB conforming to EN/ISO 3746   |
| Pressure                              | 25 bar  |
| Flow Rate                             | Internal circuit: 280 m3/h at 50/60 Hz<br>External circuit: 280 m3/h at 50/60 Hz  |
| Net Weight                            | 17 kg   |

| Cooling Gas Type | R134a (0.13 kg)  |  |
|------------------|--|--|
| Type Of Filter   | Optional external circuit filter                               |  |
| Protection Type  | Thermal protection: T 4 A Short-circuit protection (magnetic): |  |
| Material         | Steel  |  |
| Colour           | Grev (RAL 7035)  |  |

### **Environment**

| Product Certifications  | CE   |  |
|-------------------------|--|--|
| Directives              | 2004/108/EC - electromagnetic compatibility 2006/95/EC - low voltage directive 2006/42/EC - machinery                              |  |
| Standards               | EN 60335-2-40<br>EN 378<br>EN/ISO 12100<br>EN 60204-1<br>EN 60335-1  |  |
| Ip Degree Of Protection | Degree Of Protection IP55 conforming to IEC 60529 (on the internal circuit) IP34 conforming to IEC 60529 (on the external circuit) |  |

## **Packing Units**

| Unit Type Of Package 1       | PCE      |
|------------------------------|----------|
| Number Of Units In Package 1 | 1        |
| Package 1 Height             | 13.5 cm  |
| Package 1 Width              | 34.0 cm  |
| Package 1 Length             | 52.5 cm  |
| Package 1 Weight             | 17.0 kg  |
| Unit Type Of Package 2       | P12      |
| Number Of Units In Package 2 | 14       |
| Package 2 Height             | 142.0 cm |
| Package 2 Width              | 80.0 cm  |
| Package 2 Length             | 120.0 cm |
| Package 2 Weight             | 258.0 kg |

### **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

| <b>Ø</b> | Reach Free Of Svhc         |     |
|----------|----------------------------|-----|
| <b>⊘</b> | Toxic Heavy Metal Free     |     |
| <b>⊘</b> | Mercury Free               |     |
| <b>⊘</b> | Rohs Exemption Information | Yes |

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant EU RoHS Declaration   |
| China Rohs Regulation    | China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)                                   |
| Environmental Disclosure | Product Environmental Profile   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | End of Life Information   |