Product datasheet

Specifications

Green Premium™

Discontinued

ClimaSys outdoor cooling unit side of enclosure - 2900W at 400 V

Local distributor code:

402656146 NSYCUHD3K3P4

Discontinued on: 16 Apr 2024

EAN Code: 3606480676864

Main

Range	ClimaSys
Product Name	CU
Product Or Component Type	Cooling unit
Mounting Type	Side
Installation	Outdoor side
Product Destination	For enclosure
Mounting Mode	By screws
Supply Voltage	400 V AC at 50/60 Hz, 3 phases
Rated Power	2900 W
Cooling Power	2900 W 50/60 Hz L35-L35 2250 W 50/60 Hz L35-L50

Complementary

Height	1270 mm
Width	500 mm
Depth	336 mm
[In] Rated Current	2.6 A
Inrush Current	14 A
Power Consumption In W	1220 W at 50/60 Hz, L35-L35 1440 W at 50/60 Hz, L35-L50
Energy Efficiency Ratio	2.4
Control Type	Mechanical
Temperature Setting Range	20…50 °C
Ambient Air Temperature For Operation	20…46 °C inside the enclosure: 55 °C maximum: -20…50 °C outside the enclosure:
Noise Level	70 dB conforming to EN/ISO 3746
Pressure	25 bar
Flow Rate	Internal circuit: 1450 m3/h at 50/60 Hz External circuit: 1450 m3/h at 50/60 Hz
Net Weight	84 kg
Cooling Gas Type	R134a (0.84 kg)
Type Of Filter	Optional external circuit filter

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Protection Type	Thermal protection: T 6 A Short-circuit protection (magnetic):
Material	Steel
Colour	Grey (RAL 7035)

Environment

Product Certifications	CE
Directives	2006/42/EC - machinery 2006/95/EC - low voltage directive 2004/108/EC - electromagnetic compatibility
Standards	EN/ISO 12100 EN 60335-1 EN 60204-1 EN 60335-2-40 EN 378
Ip Degree Of Protection	IP55 conforming to IEC 60529 (on the internal circuit) IP34 conforming to IEC 60529 (on the external circuit)

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	156.0 cm
Package 1 Width	59.0 cm
Package 1 Length	68.0 cm
Package 1 Weight	84.125 kg

Contractual warranty

Warranty	18 months

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Transparency RoHS/REACh

Well-being performance

- Reach Free Of Svhc
- Toxic Heavy Metal Free
- Mercury Free
- Rohs Exemption Information — Yes

Certifications & Standards

Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information