# Product datasheet

Specifications

## ClimaSys forced vent. IP54, 38m3/h, 24V DC, with outlet grille and filter G2

Local distributor code:

388827633 NSYCVF38M24DPF

**EAN Code: 3606480151187**

## Main

| | |
|---|---|
| **Range** | ClimaSys |
| **Product Name** | ClimaSys CV |
| **Product Or Component Type** | Fan |
| **Type Of Filter** | Standard |
| **Flow Rate** | Free flow rate with standard filter: 58 m3/h |
| **[Us] Rated Supply Voltage** | 10...27.6 V |
| **Input Voltage** | 24 V DC |

## Complementary

| | |
|---|---|
| **Absorbed Power** | 3.6 W |
| **[In] Rated Current** | 0.18 A |
| **Noise Level < At** | 40…41 dB |
| **Bearing Type** | Ball |
| **Height** | External: 137 mm |
| **Width** | External: 117 mm |
| **Depth** | External : 49 mm |
| **Cut-Out Dimensions** | 92 x 92 mm |
| **Net Weight** | 0.23 kg |
| **Material** | Outlet grille: injected thermoplastic (ASA PC) |
| **Colour** | Outlet grille: grey (RAL 7035) |
| **Ambient Air Temperature For Operation** | -10…70 °C |
| **Ambient Air Temperature For Storage** | -40…70 °C |
| **Maximum Pressure** | 29 Pa flow rate 0 m³/h |
| **Connections - Terminals** | Cable |
| **Ip Degree Of Protection** | IP54 |
| **Device Composition** | 1 axial motor<br>2 protective grille: on the front and rear surfaces<br>1 filter: front of axial motor<br>1 outlet grille: front<br>1 cut-out template |
| **Condition Of Use** | Flow rates depends on the work point, see ProClima software<br>Filter must be cleaned and replaced regularly<br>Overfrequent filter replacement should be avoided<br>Surrounding environment must be relatively clean<br>Outside temperature must be 5 °C lower than inside temperature |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Packing Units

| | |
|---|---|
| **Unit Type Of Package 1** | PCE |
| **Number Of Units In Package 1** | 1 |
| **Package 1 Height** | 7 cm |
| **Package 1 Width** | 12 cm |
| **Package 1 Length** | 14.8 cm |
| **Package 1 Weight** | 282 g |
| **Unit Type Of Package 2** | P12 |
| **Number Of Units In Package 2** | 640 |
| **Package 2 Height** | 120 cm |
| **Package 2 Width** | 80 cm |
| **Package 2 Length** | 114 cm |
| **Package 2 Weight** | 199 kg |

## Contractual warranty

| | |
|---|---|
| **Warranty** | 18 months |

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-$CO_2$ products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Transparency RoHS/REACh

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

| | |
|---|---|
| **Reach Regulation** | REACh Declaration |
| **Eu Rohs Directive** | Compliant with Exemptions |
| **China Rohs Regulation** | China RoHS declaration<br>Product out of China RoHS scope. Substance declaration for your information |
| **Environmental Disclosure** | Product Environmental Profile |
| **Circularity Profile** | End of Life Information |