

off-delay timing relay with control contact - 0.05..1 s - 24 V AC DC - 1OC

RE7RM11BU

! Discontinued on: 1 Jun 2016



EAN Code: 3389110311969

Main

Range Of Product	Zelio Time
Product Or Component Type	Industrial timing relay
Component Name	RE7
Time Delay Type	С
Time Delay Range	0.05 s300 h

Complementary

Discrete Output Type	Relay
Contacts Material	90/10 silver nickel contacts
Width Pitch Dimension	22.5 mm
[Us] Rated Supply Voltage	110240 V AC 50/60 Hz 24 V AC/DC 50/60 Hz 4248 V AC/DC 50/60 Hz
Voltage Range	0.851.1 Us
Connections - Terminals	Screw terminals, 2 x 1.5 mm² flexible with cable end Screw terminals, 2 x 2.5 mm² flexible without cable end
Tightening Torque	0.61.1 N.m
Setting Accuracy Of Time Delay	+/- 10 % of full scale
Repeat Accuracy	+/- 0.2 %
Temperature Drift	< 0.07 %/°C
Voltage Drift	< 0.2 %/V
Minimum Pulse Duration	20 ms
Reset Time	50 ms
Maximum Switching Voltage	250 V AC/DC
Mechanical Durability	20000000 cycles
[Ith] Conventional Free Air Thermal Current	8 A
Maximum [le] Rated Operational Current	2 A DC-13 24 V at 70 °C conforming to IEC 60947-5-1/1991/VDE 0660 0.1 A DC-13 250 V at 70 °C conforming to IEC 60947-5-1/1991/VDE 0660 0.2 A DC-13 115 V at 70 °C conforming to IEC 60947-5-1/1991/VDE 0660 3 A AC-15 at 70 °C conforming to IEC 60947-5-1/1991/VDE 0660
Minimum Switching Capacity	at 12 V 10 mA
Input Voltage	< 60 V X1Z2 terminal(s) < 60 V Y1Z2 terminal(s)

Maximum Switching Current	1 mA (X1Z2) 1 mA (Y1Z2)	
Input Compatibility	3/4 wires sensors PNP/NPN without internal load <50 m X1Z2 terminal(s) 3/4 wires sensors PNP/NPN without internal load <50 m Y1Z2 terminal(s)	
Potentiometer Characteristic	Linear 47 kOhm (+/- 20 %), 0.2 W, cable length <25 m Z1Z2 terminal(s)	
Marking	CE	
Overvoltage Category	III conforming to IEC 60664-1	
[Ui] Rated Insulation Voltage	250 V between contact circuit and control inputs IEC certified 250 V between contact circuit and power supply IEC certified 300 V between contact circuit and control inputs CSA certified 300 V between contact circuit and power supply CSA certified	
Supply Disconnection Value	> 0.1 Uc	
Operating Position	Any position without derating	
Surge Withstand	2 kV conforming to IEC 61000-4-5 level 3	
Power Consumption In Va	0.7 VA at 24 V 1.6 VA at 48 V 1.8 VA at 110 V 8.5 VA at 240 V	
Maximum Power Consumption In W	0.5 W at 24 V 1.2 W at 48 V	
Terminal Description	(15-16-18)OC_OFF ALT (B1-A2)CO (Z1)UNUSED (Z2)UNUSED (X1)UNUSED (Y1)UNUSED	
Height	78 mm	
Width	22.5 mm	
Depth	80 mm	
Net Weight	0.15 kg	

Environment

Immunity To Microbreaks	3 ms
Standards	EN/IEC 61812-1
Product Certifications	UL
	GL
	CSA
Ambient Air Temperature For Storage	-4085 °C
Ambient Air Temperature For Operation	-2060 °C
Relative Humidity	1585 % 3K3 conforming to IEC 60721-3-3
Vibration Resistance	0.35 mm (f= 1055 Hz) conforming to IEC 60068-2-6
Shock Resistance	15 gn for 11 ms conforming to IEC 60068-2-27
Ip Degree Of Protection	IP20 (terminals)
	IP50 (housing)
Pollution Degree	3 conforming to IEC 60664-1
Dielectric Strength	2.5 kV
Non-Dissipating Shock Wave	4.8 kV
Resistance To Electrostatic	6 kV in contact conforming to IEC 61000-4-2 level 3
Discharge	8 kV in air conforming to IEC 61000-4-2 level 3

Resistance To Electromagnetic Fields	10 V/m conforming to IEC 61000-4-3 level 3
Resistance To Fast Transients	2 kV conforming to IEC 61000-4-4 level 3
Disturbance Radiated/Conducted	CISPR 11 group 1 - class A CISPR 22 - class A

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1


Contractual warranty

Warranty 18 months


Dimensions Drawings

Width 22.5 mm

Rail Mounting



Screw Fixing



Product datasheet

RE7RM11BU


Connections and Schema

Internal Wiring Diagram

A1	15	B1
Z1		B2
A2 B2) ₆	18 15
X1	¥1	Z2
18	16	A2

Recommended Application Wiring Diagram


Start by External Control



- 1 Supply
- **2** 12...48 V
- **3** 24 V

Recommended Application Wiring Diagram

Start by External Control




- 1 Supply
- **2** 12...48 V
- **3** 24 V


RE7RM11BU

Control of Several Relays

Control of several relays with a single external control contact




Connection of an External Control Contact Without Using Terminal Z2



Direct current supply only.


It is advisable to follow the recommended wiring schemes detailed above if the restrictions given are taken into account.



Direct current supply only.


It is advisable to follow the recommended wiring schemes detailed above if the restrictions given are taken into account.

Connection 3-Wire NPN or PNP Sensor




Connection 3-Wire NPN or PNP Sensor Without Using Terminal Z2

Connection NPN




It is advisable to follow the recommended wiring schemes detailed above if the restrictions given are taken into account.

Connection PNP



It is advisable to follow the recommended wiring schemes detailed above if the restrictions given are taken into account.

Connection of Potentiometer




Connection Precautions



UNEXPECTED EQUIPMENT OPERATION

No galvanic isolation between supply terminals and control inputs.

Failure to follow these instructions can result in death, serious injury, or equipment damage.




Performance Curves

Performance Curves

A.C. Load Curve 1


Electrical durability of contacts on resistive loading millions of operating cycles



X Current broken in A Y Millions of operating cycles

A.C. Load Curve 2

Reduction factor k for inductive loads (applies to values taken from durability curve 1).



\boldsymbol{X} Power factor on breaking (cos $\boldsymbol{\varphi}$)

Y Reduction factor k

Example: An LC1-F185 contactor supplied with 115 V/50 Hz for a consumption of 55 VA or a current consumption equal to 0.1 A and $\cos \phi = 0.3$. For 0.1 A, curve 1 indicates a durability of approximately 1.5 million operating cycles. As the load is inductive, it is necessary to apply a reduction coefficient k to this number of cycles as indicated by curve 2.


For $\cos \phi = 0.3$: k = 0.6 The electrical durability therefore becomes:1.5 10^6 operating cycles x 0.6 = 900 000 operating cycles.



D. C. Load Limit Curve

Product datasheet

RE7RM11BU



- X Current in A
- Y Voltage in V
- **1** L/R = 20 ms
- 2 L/R with load protection diode
- 3 Resistive load

RE7RM11BU


Technical Description

Function C: Off-Delay Relay with Control Signal


Description

After power-up and closing of the control contact C, the output R closes. When control contact C re-opens, timing T starts. At the end of the timing period, the output(s) R revert(s) to its/their initial state. The second output can be either timed or instantaneous

Function: 1 Output



Function: 2 Outputs



2 timed outputs (R1/R2) or 1 timed output (R1) and 1 instantaneous output (R2 inst.)

RE7RM11BU

Legend

	Relay de-energised	
	Relay energised	
	Output open	
	Output closed	
С	Control contact	
G	Gate	
R	Relay or solid state output	
R1/R2	2 timed outputs	
R2 inst.	The second output is instantaneous if the right position is selected	
Т	Timing period	
Та -	Adjustable On-delay	
Tr -	Adjustable Off-delay	
U	Supply	