Product datasheet

Specification





TeSys Vario enclosed, emergency switch disconnector, 25A, UL/CSA

Local distributor code: 403019423

3019423 VC2GUN

EAN Code: 3389119413183

Main

Range	TeSys
Product Name	TeSys VARIO
Device Short Name	VC-GUN
Product Or Component Type	Enclosed emergency stop switch disconnector
Performance Level	High performance
Poles Description	3P
Control Type	Rotary handle
Handle Colour	Red
Handle Front Plate Colour	Yellow
Rotary Handle Padlocking	1 to 3 padlocks 48 mm

Complementary

Marking	0 - 1
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ithe] Conventional Enclosed Thermal Current	32 A
[le] Rated Operational Current	29 A (AC-23A) at 400 V
Rated Operational Power In W	15 kW at 400 V (AC-23) 11 kW at 400 V (AC-3)
Intermittent Duty Class	30
Making Capacity (I Rms)	400 A at 400 V AC-21A 400 A at 400 V AC-22A 400 A at 400 V AC-23A
[Icm] Rated Short-Circuit Making Capacity	1 kA at 400 V at Ipeak
[Ith] Conventional Free Air Thermal Current	32.0 A conforming to IEC 690 V 25 A conforming to UL 600 V
Rated Power In Hp	5 hp at 240 V, UL certified 10 hp at 480 V, UL certified 15 hp at 600 V, UL certified
[Icw] Rated Short-Time Withstand Rms Current	480 A at 400 V duration: 1 s
Rated Conditional Short-Circuit Current	10 kA at 400 V - associated fuse 50 A aM 10 kA at 400 V - associated fuse 50 A gG
Breaking Capacity	320 A at 400 V (AC-21A) 320 A at 400 V (AC-22A) 320 A at 400 V (AC-23A)

6 May 2024 Life Is On Schneider

Mechanical Durability	100000 cycles	
Electrical Durability	100000 cycles AC-21 30000 cycles DC-15	
Environmental Characteristic	Standard environment	
Suitability For Isolation	Yes	
Connections - Terminals	Screw clamp terminals10 mm² - solid - with cable end Screw clamp terminals6 mm² - flexible	
Tightening Torque	2.1 N.m - on screw clamp terminals	
Fire Resistance	960 °C conforming to IEC 60595-2-1	
Handle Front Plate Dimension	60 x 60 mm	
Height	164 mm	
Width	121 mm	
Depth	132 mm	
Net Weight	0.5 kg	

Environment

Standards	IEC 60204 CSA C22.2 No 14 UL 508 IEC 60947-4-1	
Protective Treatment	тс	
Ip Degree Of Protection	IP65 conforming to IEC 60529	
Nema Degree Of Protection	NEMA 12	
Mechanical Robustness	Vibrations 10150 Hz (1 gn) conforming to IEC 60068-2-6 Shocks 11 ms (30 Gn) conforming to IEC 60068-2-27	
Ambient Air Temperature For	-2050 °C	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	13.500 cm
Package 1 Width	18.500 cm
Package 1 Length	14.000 cm
Package 1 Weight	647.0 g
Unit Type Of Package 2	S04
Number Of Units In Package 2	16
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	11.133 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations