# **Product datasheet**

Specification





# TeSys Vario enclosed, emergency switch disconnector, 63A, UL/CSA

Local distributor code:

403019672 VC4GUN

EAN Code: 3389119413206

## Main

Range	TeSys	
Product Name	TeSys VARIO	
Device Short Name	VC-GUN	
Product Or Component Type	Enclosed emergency stop switch disconnector	
Performance Level	High performance	
Poles Description	3P	
Control Type	Rotary handle	
Handle Colour	Red	
Handle Front Plate Colour	e Colour Yellow	
Rotary Handle Padlocking	1 to 3 padlocks 48 mm	

### Complementary

Complementary	
Marking	0 - 1
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ithe] Conventional Enclosed Thermal Current	63 A
[le] Rated Operational Current	57 A (AC-23A) at 400 V
Rated Operational Power In W	30 kW at 400 V (AC-23) 22 kW at 400 V (AC-3)
Intermittent Duty Class	30
Making Capacity ( I Rms)	800 A at 400 V AC-21A 800 A at 400 V AC-22A 800 A at 400 V AC-23A
[Icm] Rated Short-Circuit Making Capacity	2.1 kA at 400 V at Ipeak
[Ith] Conventional Free Air Thermal Current	63.0 A conforming to IEC 690 V 63 A conforming to UL 600 V
Rated Power In Hp	15 hp at 240 V, UL certified 30 hp at 480 V, UL certified 40 hp at 600 V, UL certified
[Icw] Rated Short-Time Withstand Rms Current	960 A at 400 V duration: 1 s
Rated Conditional Short-Circuit Current	10 kA at 400 V - associated fuse 80 A aM 10 kA at 400 V - associated fuse 80 A gG
Breaking Capacity	640 A at 400 V (AC-21A) 640 A at 400 V (AC-22A) 640 A at 400 V (AC-23A)

Mechanical Durability	30000 cycles
Electrical Durability	30000 cycles AC-21 30000 cycles DC-15
Environmental Characteristic	Standard environment
Suitability For Isolation	Yes
Connections - Terminals	Screw clamp terminals25 mm² - solid - with cable end Screw clamp terminals16 mm² - flexible
Tightening Torque	4 N.m - on screw clamp terminals
Fire Resistance	960 °C conforming to IEC 60595-2-1
Handle Front Plate Dimension	60 x 60 mm
Height	193 mm
Width	164 mm
Depth	132 mm
Net Weight	0.93 kg

## **Environment**

Standards	UL 508 CSA C22.2 No 14 IEC 60947-4-1 IEC 60204	
Protective Treatment	тс	
Ip Degree Of Protection	IP65 conforming to IEC 60529	
Nema Degree Of Protection	egree Of Protection NEMA 12	
Mechanical Robustness	Vibrations 10150 Hz (1 gn) conforming to IEC 60068-2-6 Shocks 11 ms (30 Gn) conforming to IEC 60068-2-27	
Ambient Air Temperature For Operation	-2050 °C	

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	21 cm
Package 1 Width	21.5 cm
Package 1 Length	22 cm
Package 1 Weight	1.062 kg
Unit Type Of Package 2	P06
Number Of Units In Package 2	4
Package 2 Height	77 cm
Package 2 Width	80 cm
Package 2 Length	60 cm
Package 2 Weight	13.162 kg

# **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance

<b>②</b>	Toxic Heavy Metal Free	
	Mercury Free	
<b>②</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations