

braking resistor - 27 ohm - 400 W - cable 3 m - IP65

VW3A7604R30

EAN Code: 3389119207195

Main

Range Of Product	Lexium
	Altivar
Range Compatibility	Lexium 05
	Lexium 28
	Lexium 32i
	Lexium 52
	Altivar 32
	Lexium 15
	Altivar Machine ATV320
	Lexium 32
	Easy Lexium 16
Product Compatibility	ATV32HU55N4
	ATV32HU75N4
	Variable speed drive ATV320 at 5.5 kW, 380500 V, three phase
	Variable speed drive ATV320 at 7.5 kW, 380500 V, three phase
	Variable speed drive ATV320 at 5.5 kW, 525600 V, three phase
	Variable speed drive ATV320 at 7.5 kW, 525600 V, three phase
	Motion servo drive LXM16D at 0.75 kW, 200230 V, single phase
	Motion servo drive LXM16D at 1 kW, 200230 V, single phase
	Motion servo drive LXM16D at 1.5 kW, 200230 V, single phase
Product Or Component Type	Braking resistor
Ohmic Value	27 Ohm

Complementary

Energy Peak	10500 J at 480 V 11400 J at 400 V 18100 J at 230 V 25500 J at 115 V	
Average Power Available	100 W at 50 °C	
Continuous Power	400 W	
Protection Type	Thermal protection via the servo drive	
Net Weight	1.62 kg	
Cable Length	3 m	

Environment

Ip Degree Of Protection	IP65
Ambient Air Temperature For Storage	-2585 °C
Ambient Air Temperature For Operation	050 °C

Packing Units

Unit Type Of Package 1 PCE

Number Of Units In Package 1	1
Package 1 Height	4.500 cm
Package 1 Width	13.000 cm
Package 1 Length	40.000 cm
Package 1 Weight	1.725 kg
Unit Type Of Package 2	S03
Number Of Units In Package 2	6
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	11.273 kg
Unit Type Of Package 3	S06
Number Of Units In Package 3	48
Package 3 Height	73.500 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	96.472 kg

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance


Reach Free Of Svhc		
Mercury Free		
Rohs Exemption Information	Yes	
Pvc Free		
Reach Regulation	REACh Declaration	
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
China Rohs Regulation	China RoHS declaration	

VW3A7604R30

Dimensions Drawings

Braking Resistor

Dimensions



Dimensions in mm

b	b1	С	с1	Н
257	216	30	_	204

Dimensions in in.

b	b1	С	с1	Н
10.11	8.50	1.18	_	8.03