Product datasheet

Specifications





Illuminated unit for modular tower lights, plastic, red, Ø70, integral "flash" discharge tube, 10 joule, 24 V AC/DC

Local distributor code: 388813867

XVBC8B4

EAN Code: 3389110845679

Main

Product Or Component Type Indicator bank Beacon Or Indicator Bank Unit Type Illuminated unit Signalling Type Flashing Mounting Diameter 70 mm Component Name XVBC Material Polycarbonate Light Source Integral flash discharge tube, red Bulb Type Flash discharge tube 24 V AC/DC 24 V AC/DC		
Beacon Or Indicator Bank Unit Type Illuminated unit Signalling Type Flashing Mounting Diameter 70 mm Component Name XVBC Material Polycarbonate Light Source Integral flash discharge tube, red Bulb Type Flash discharge tube 24 V AC/DC 24 V AC/DC	Range Of Product	Harmony XVB Universal
Type Flashing Signalling Type Flashing Mounting Diameter 70 mm Component Name XVBC Material Polycarbonate Light Source Integral flash discharge tube, red Bulb Type Flash discharge tube YUS] Rated Supply Voltage 24 V AC/DC	Product Or Component Type	Indicator bank
Mounting Diameter 70 mm Component Name XVBC Material Polycarbonate Light Source Integral flash discharge tube, red Bulb Type Flash discharge tube YUS] Rated Supply Voltage 24 V AC/DC	Beacon Or Indicator Bank Unit Type	Illuminated unit
Component Name XVBC Material Polycarbonate Light Source Integral flash discharge tube, red Bulb Type Flash discharge tube YUS] Rated Supply Voltage 24 V AC/DC	Signalling Type	Flashing
Waterial Polycarbonate Light Source Integral flash discharge tube, red Bulb Type Flash discharge tube 24 V AC/DC	Mounting Diameter	70 mm
Light Source Integral flash discharge tube, red Bulb Type Flash discharge tube (Us] Rated Supply Voltage 24 V AC/DC	Component Name	XVBC
Bulb Type Flash discharge tube (Us] Rated Supply Voltage 24 V AC/DC	Material	Polycarbonate
Us] Rated Supply Voltage 24 V AC/DC	Light Source	Integral flash discharge tube, red
	Bulb Type	Flash discharge tube
Flash Energy 10 J	[Us] Rated Supply Voltage	24 V AC/DC
	Flash Energy	10 J

Complementary

Assembly Style	Customer assembly, up to 5 units
Connections - Terminals	Screw clamp terminals, <= 1 x 1.5 mm ² with cable end
[Ui] Rated Insulation Voltage	250 V conforming to IEC 60947-1
Nominal Voltage Limit	0.851.1 Un conforming to IEC 60947-5-1
Current Consumption	< 1300 mA AC < 850 mA DC
[Uimp] Rated Impulse Withstand Voltage	4 kV conforming to IEC 60947-1
Flashing Frequency	1 Hz
Cad Overall Width	70 mm
Cad Overall Height	157 mm
Cad Overall Depth	70 mm
Net Weight	0.305 kg

Environment

Product Certifications	CCC EAC CSA C22-2 No 14 UL 508
Standards	IEC 60947-5-1
Protective Treatment	тс

Ambient Air Temperature For Storage	-4070 °C
Electrical Shock Protection Class	Class I on support tube conforming to IEC 61140 Class II on base unit conforming to IEC 61140
Ip Degree Of Protection	IP65 on fixing base XVBZ0. conforming to IEC 60529 IP66 on base unit conforming to IEC 60529
Nema Degree Of Protection	Type 4X conforming to UL (indoor)

Packing Units

PCE
1
8.0 cm
8.0 cm
19.0 cm
320.0 g
S03
12
30.0 cm
30.0 cm
40.0 cm
4.307 kg

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance



Rohs Exemption Information

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations


Product datasheet

Dimensions Drawings

Indicator Bank with "Flash" Discharge Tube Unit

Dimensions

Below drawing shows the minimum configuration of the product. Select the number of stages according to the product characteristics in order to get \mathbf{b} dimension.



- (1) Base unit XVBC07, to be ordered separately
- (2) Illuminated or audible signalling unit XVBC ..., to be ordered separately
- (3) "Flash" unit

Number of illuminated or audible signalling units other than "flash" tube	b in mm	b in in.
1	295	11.61
2	358	14.09
3	421	16.57
4	484	19.06