Product datasheet

Specifications





orange light block with body/fixing collar integral LED 110...120V

Local distributor code: 237093424

ZB4BVG5

! Discontinued on: 31 Jan 2023

! End-of-service on: 5 Apr 2023

! Discontinued

Important message: All colored LED are replaced with a single Universal LED block for use with new illuminated heads (more information at se.com/harmonyxb4 or se.com/harmonyxb5) EAN Code: 3389110892468

Main

| Range Of Product | Harmony XB4 |
|-------------------------------|--|
| Product Or Component Type | Complete body/light block assembly |
| Device Short Name | ZB4 |
| Fixing Collar Material | Zamak |
| Sale Per Indivisible Quantity | 1 |
| Connections - Terminals | Screw clamp terminals, <= 2 x 1.5 mm² with cable end Screw clamp terminals, >= 1 x 0.22 mm² without cable end |
| Light Source | Protected LED |
| Bulb Base | Integral LED |
| Light Source Colour | Orange |
| [Us] Rated Supply Voltage | 110120 V AC at 50/60 Hz |

Complementary

| Cad Overall Width | 30 mm |
|--|--|
| Cad Overall Height | 47 mm |
| Cad Overall Depth | 37 mm |
| Terminals Description Iso N°1 | (X1-X2)PL |
| Net Weight | 0.054 kg |
| Tightening Torque | 0.81.2 N.m conforming to EN 60947-1 |
| Shape Of Screw Head | Cross compatible with Philips no 1 screwdriver Cross compatible with pozidriv No 1 screwdriver Slotted compatible with flat Ø 4 mm screwdriver Slotted compatible with flat Ø 5.5 mm screwdriver |
| [Ui] Rated Insulation Voltage | 600 V (pollution degree 3) conforming to EN 60947-1 |
| [Uimp] Rated Impulse Withstand Voltage | 6 kV conforming to EN 60947-1 |
| Signalling Type | Steady |
| Current Consumption | 14 mA |
| Service Life | 100000 h at rated voltage and 25 °C |
| Surge Withstand | 1 kV conforming to IEC 61000-4-5 |
| Device Presentation | Basic sub-assemblies |

Environment

| Protective Treatment | тн |
|--|---|
| Ambient Air Temperature For Storage | -4070 °C |
| Ambient Air Temperature For Operation | -4070 °C |
| Electrical Shock Protection Class | Class I conforming to IEC 60536 |
| Standards | EN/IEC 60947-5-4 EN/IEC 60947-5-1 CSA C22.2 No 14 EN/IEC 60947-1 UL 508 JIS C8201-5-1 EN/IEC 60947-5-5 JIS C8201-1 |
| Product Certifications | LROS (Lloyds register of shipping) GL UL listed BV CSA DNV |
| Vibration Resistance | 5 gn (f= 2500 Hz) conforming to IEC 60068-2-6 |
| Shock Resistance | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27 |
| Resistance To Fast Transients | 2 kV conforming to IEC 61000-4-4 |
| Resistance To Electromagnetic Fields | 10 V/m conforming to IEC 61000-4-3 |
| Resistance To Electrostatic Discharge | 6 kV on contact (on metal parts) conforming to IEC 61000-2-6 8 kV in free air (in insulating parts) conforming to IEC 61000-2-6 |
| Electromagnetic Emission | Class B conforming to IEC 55011 |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 3.600 cm |
| Package 1 Width | 5.500 cm |
| Package 1 Length | 6.000 cm |
| Package 1 Weight | 52.0 g |
| Unit Type Of Package 2 | S03 |
| Number Of Units In Package 2 | 200 |
| Package 2 Height | 30.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 10.895 kg |
| Unit Type Of Package 3 | P06 |
| Number Of Units In Package 3 | 1600 |
| Package 3 Height | 77.000 cm |
| Package 3 Width | 80.000 cm |
| Package 3 Length | 60.000 cm |
| Package 3 Length | 60.000 cm |

Package 3 Weight

100.284 kg

Contractual warranty

Warranty

17 May 2024

18 months

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards


| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | End of Life Information |

Product datasheet

ZB4BVG5

Dimensions Drawings

Dimensions




ZB4BVG5


Mounting and Clearance

Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)

Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board

Connection by Faston Connectors





- (1) Diameter on finished panel or support
- (2) 40 mm min. / 1.57 in. min.
- (3) 30 mm min. / 1.18 in. min.
- (4) Ø 22.5 mm / 0.89 in. recommended (Ø 22.3 mm $_0^{+0.4}$ / 0.88 in. $_0^{+0.016}$)
- (5) 45 mm min. / 1.78 in. min.
- (6) 32 mm min. / 1.26 in. min.